

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
(**EIGHTH STANDARD PARALLEL SOUTH**)
TOWNSHIP 40 SOUTH, RANGE 24 EAST

THE DEPENDENT RESURVEY OF THE SOUTH BOUNDARY (**EIGHTH
STANDARD PARALLEL SOUTH**), TOWNSHIP 40 SOUTH, RANGE 25 EAST

THE DEPENDENT RESURVEY OF THE EAST, SOUTH AND WEST BOUNDARIES

THE DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES

THE SUBDIVISION OF A PORTION OF SECTION 27

THE NEW MEANDER OF THE RIGHT BANK OF THE SAN JUAN RIVER

THE ORIGINAL SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

THE ORIGINAL MEANDER OF THE LEFT BANK OF THE SAN JUAN RIVER

AND

METES-AND-BOUNDS SURVEYS IN SECTION 27

IN

TOWNSHIP 41 SOUTH, RANGE 25 EAST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

John F. Carroll
Cadastral Surveyor

Under special instructions dated **February 3, 2004**,
approved **February 3, 2004**, which provided for the surveys
included under Group Number **973** and assignment instructions
dated **February 3, 2004**.

Survey commenced **February 17, 2004**
Survey completed **June 30, 2005**

INDEX DIAGRAM

Township 41 South, Range 25 East, Salt Lake Meridian, Utah.

3 4	4 5	6 6	7 7	8 9	9 10 11
23 6	63 5	59 4	55 3	46 2	36 1 12
23 63	61 62	58 58	54 54	45 45	35 36 12
24 7	61 8	58 9	54 10	44 11	34 12 13
24 47	48 48	48 49	49 50	43 44	33 34 13
AUXILIARY		BASE	LINE		
26 18	59 17	56 16	50 15	43 14	33 13 13
26 86	60 61	56 57	51 51	42 43	32 33 14
26 19	86 20	82 21	51 22	42 23	32 24 14
27 85	85 85	82 82	52 53	40 41	31 31 15
27 30	84 29	81 28	80 27	39 26	30 25 15
27 84	83 84	80 81	79 38	37 38	29 30 15
28 31	83 32	80 33	79 34	37 35	29 36 16
22 22	22 21	21 21	21 20	19 19	18 18 16

The Subdivision of Section 27.....Page 63
The Resurvey of the Right Bank Meanders of the San Juan River....Page 69
The Survey of the Left Bank Meanders of the San Juan River.....Page 73
The Survey of the Westerly Boundary of Tract 37, in Section 27...Page 77
The Informative Traverse of the Centerline of Highway No. 262....Page 87

TOWNSHIP 41 SOUTH, RANGE 25 EAST, SALT LAKE MERIDIAN, UTAH.

The following field notes are those of the dependent resurvey of a portion of the south boundary (Eighth Standard Parallel South), Township 40 South, Range 24 East, the south boundary (Eighth Standard Parallel South), Township 40 South, Range 25 East, the dependent resurvey of the east, south and west boundaries, the dependent resurvey of a portion of the subdivisional lines, the subdivision of a portion of section 27, the new meander of the right bank of the San Juan River, the original survey of a portion of the subdivisional lines, the original meander of the left bank of the San Juan River and the metes-and-bounds survey in section 27, in T. 41 S., R. 25 E., Salt Lake Meridian, Utah.

History of Surveys**T. 40 S., R. 24 E., Salt Lake Meridian, Utah.**

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY (Eight Standard Parallel South)			
All	H.D. Page & J.M. Lentz	1899	
Portion			M.D. Cazier 2003

T. 41 S., R. 25 E., Salt Lake Meridian, Utah.**SOUTH BOUNDARY**

Portion	H.D. Page & J.M. Lentz	1899	
Portion	A. Nelson & R.G. Yundt	1953	A. Nelson & R.G. Yundt 1953

EAST BOUNDARY

All	H.D. Page & R.G. Yundt	1899
-----	---------------------------	------

WEST BOUNDARY

Portion	H.D. Page & J.M. Lentz	1899	
Portion	A. Nelson & R.G. Yundt	1953	A. Nelson & R.G. Yundt 1953

NORTH BOUNDARY (Eight Standard Parallel South)

All	A.D. Ferron	1884	
All			H.D. Page & J.M. Lentz 1899
Portion			M.D. Cazier 2003

TOWNSHIP 41 SOUTH, RANGE 25 EAST, SALT LAKE MERIDIAN, UTAH.

SUBDIVISION

All H.D Page &
 J.M. Lentz 1899

LOCAL SUBDIVISION

Portion Office of Navajo Land Development, The Navajo Tribe 1982

Portion M.U. Bagwell 1957

Tract 37, a portion of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line. Tract 38, as described in Exhibit "A" the withdrawal of Aneth Federal School from Tribal lands. Parcel A as described in Exhibit "B" located within the Group File is relinquished from government withdrawn lands.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 973, dated February 3, 2004.

The direction of the lines were determined by mean geodetic inverse between corners. Global Positioning System (GPS) utilizing Real-time kinematic (RTK) was used throughout the survey. Cadastral Measurement Management (CMM) was utilized during the course of the survey.

Preliminary to the resurvey, the lines of the original survey were retraced and a diligent search was made for any evidence of the original field note record. The retracement data were thoroughly verified and only the true line notes are given herein.

The geographic position of the 1/4 section corner of sections 26 and 27, T. 41 S., R. 25 E., Salt Lake Meridian, Utah is as follows:

Latitude: 37°11'35.782" N. Longitude: 109°09'07.202" W.
N.A.D. 1983 (CORS96)

and the geographic position of the township corner of Townships 41 and 42 South, Ranges 25 and 26 East., Salt Lake meridian, Utah is as follows:

Latitude: 37°10'17.603" N. Longitude: 109°06'56.478" W.
N.A.D. 1983 (CORS96)

The geographic position of BLM station "TOWN", as determined by NGS OPUS solution using base stations SALT RIVER PROJECT CORS ARP, CARBON COUNTY COU CORS ARP and MYTON 1 CORS ARP is as follows:

Latitude: 37°14'28.074" N. Longitude: 109°18'17.818" W.
N.A.D. 1983 (CORS96) N.A.V.D. 4602 feet.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 24 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Dependent Resurvey of a Portion of the South Boundary,
 (Eighth Standard Parallel South),
 T. 40 S., R. 24 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
 H. D. Ferron in 1883 and the Resurveys
 Executed by H. D. Page & J. M. Lentz in 1899
 and M. Cazier in 2003

Beginning at the stan. 1/4 sec. cor. of sec. 36, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, in a mound of stone, with Navajo brass cap mkd. as described in the field notes of the 2003 resurvey record.

Cor. is located on a SE slope in scattered sagebrush.

N. 89°56.1' E., on the south bdy. of sec. 36.

- 34.477** Point for the closing cor. of secs. 1 and 6, T. 41 S., Rs. 24 and 25 E., at proportionate dist.; there is no remaining evidence of the original cor. This point is referred to as a tp. cor. in the field notes of the 1899 resurvey record but was mkd. as a closing cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T40S R24E
 S36
 ———
 S1 | S6
 ———
 CC
 T41S
 R24E R25E
 2004

- 39.916** The stan. tp. cor. of T. 40 S., Rs. 24 and 25 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above ground, with Navajo brass cap mkd. as described in the field notes of the 2003 resurvey record.

Dependent Resurvey of the South Boundary,
 (Eighth Standard Parallel South),
 T. 40 S., R. 25 E., Salt Lake Meridian, Utah

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Reestablishment of the Survey Executed by
 H. D. Ferron in 1884 and the Resurvey
 Executed by H. D. Page & J. M. Lentz in 1899

S. 89°56.5' E., on the south bdy. of sec. 31.

- 31.768** Point for the 1/4 sec. cor. of sec. 6 only, T. 41 S., R. 25 E., at proportionate dist. bet. closing cors.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock with magnet at base, with Navajo brass cap mkd.:

1/4 S6
 T41S R25E
 2004

Cor. is located on a SW slope in desert weed.

- 39.956** Point for the stan. 1/4 sec. cor. of sec. 31, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

SC
 T40S R25E
 1/4 S31

2004

Cor. is located on a SW slope, 45 ft. south of a wash, drains S. 80° W.

- 71.721** Point for the closing cor. of secs. 5 and 6, T. 41 S., R. 25 E., at proportionate dist.; there is no remaining evidence of the original cor., falls on a steep fill slope of an improved gravel road, where it is impractical to monument. No suitable place to set a witness cor. Not monumented.

from which the reference object

A power pole, 10 ins. bears S. 63°28.6'W., 194.52 ft. to PK-nail.

- 79.912** Point for the stan. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor., falls on the fill edge of an improved gravel road and in the vicinity of underground gas lines, where it is impractical and unsafe to monument.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a PK-nail flush with road surface.

from which the reference objects

A power pole, 8 ins. diam., bears N. $8^{\circ}15.9'$ E., 60.94 ft. to a PK-nail.

A power pole, 15 ins. diam., bears N. $48^{\circ}25.5'$ E., 96.73 ft. dist., to a PK-nail.

Cor. is located 25 ft. north of improved gravel road, 24 ft. wide, bears N. 75° E. and S. 75° W.

S. $89^{\circ}56.5'$ E., on the south bdy. of sec. 32.

- 31.895** Point for the $1/4$ sec. cor. of sec. 5, at midpoint bet. closing cors.

Set a stainless steel post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

$1/4 \bullet S5$
 T41S R25E
 2004

Cor. is located on a southerly slope in scattered sagebrush.

- 39.956** Point for the stan. $1/4$ sec. cor. of sec. 32, at proportionate dist.; there is no remaining evidence of the original cor., falls on south face of a ledge.

Set a stainless steel post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground to solid rock with magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

SC
 T40S R25E
 $1/4 \bullet S32$

2004

Cor. is located on the southerly slope of a ledge area, 45 ft. south of a dirt road, 16 ft. wide, bears S. 10° E. and N. 10° W.

- 71.982** Point for the closing cor. of secs. 4 and 5, T. 41 S., R. 25 E., original closing cor. found off line, hereinafter described, falls on a ledge where it is impractical to set a standard Navajo stainless steel post.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a PK-nail at point for closing cor. and on the ledge
 chisel the marks:

┌
 5 | 4
 CC

Deposit a sandstone rock, 12X16X4 ins. over PK-nail and above
 chiseled marks.

Cor. is located on a ledge, 3 ft. west of the edge.

- 79.912 The stan. cor. of secs. 32 and 33, monumented with a
 limestone, 8X11X11 ft., firmly set, on top of limestone are
 the clearly chiseled marks:

SC
 |||||

No additional improvements were made.

Cor. is located on a west slope in limestone boulders.

N. 89°59.5' E., on the south bdy. of sec. 33.

- 31.924 Point for the 1/4 sec. cor. of sec. 4, at midpoint bet.
 closing cors.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26
 ins. in the ground with magnet at base, in a mound of stone, 3
 ft. base, to top, with Navajo brass cap mkd.:

1/4 S4
 T41S R25E
 2004

Cor. is located on a northwest slope in scattered sagebrush.

- 39.977 Point for the stan. 1/4 sec. cor. of sec. 33, at proportionate
 dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 5
 ins. in the ground to solid rock with magnet at base, in a
 mound of stone, 4 ft. base, to top, with Navajo brass cap
 mkd.:

SC
 T40S R25E
 1/4 • S33

2004

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH)
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a rock ledge, bet. gas lines.

- 71.778** Point for the closing cor. of secs. 3 and 4, T. 41 S.,
R. 25 E., original closing cor. found off line, hereinafter
described.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20
ins. in the ground with magnet at base, in a collar of stone,
with Navajo brass cap mkd.:

T40S
S33
S4 | S3
CC
T41S R25E
2004

Cor. is located on a rocky east slope in sagebrush.

- 79.954** The stan. cor. of secs. 33 and 34, monumented with a
sandstone, 16X10X4 ins., loosely set, dimly mkd. with 3
notches on the west face and dimly mkd. SC on the north face,
with a reference mound of stone to the north.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 9
ins. in the ground to solid rock with magnet at base, in a
supporting mound of stone, with Navajo brass cap mkd.:

SC
T40S R25E
S33 | S34
2004

Bury mkd. stone alongside stainless steel post.

Rebuild reference mound of stone to 4 ft. base around
stainless steel post.

Cor. is located on a westerly slope in sagebrush.

N. 89°59.6' E., on the south bdy. of sec. 34.

- 31.816** Point for the 1/4 sec. cor. of sec. 3, at midpoint bet.
closing cors.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28
ins. in the ground with magnet at base, with a reference mound
of stone to the south, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
(EIGHTH STANDARD PARALLEL SOUTH)
T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T40S R25E

1/4 S3

T41S

2004

Cor. is located on gentle SE slope, approximately 150 ft. west of wash, drains S.

- 39.969** Point for the stan. 1/4 sec. cor. of sec. 34, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

SC

T40S R25E

1/4 S34

2004

Cor. is located 10 ft. south of wash, drains W.

- 71.809** Point for the closing cor. of secs. 2 and 3, T. 41 S., R. 25 E., original closing cor. found off line, hereinafter described.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 2 1/2 ft. base, to top, with Navajo brass cap mkd.:

T40S R25E

S34

S3 | S2

CC

T41S

2004

Cor. is located on a gradual SE slope in grass.

- 79.938** The stan. cor. of secs. 34 and 35, monumented with a sandstone, 20X12X6 ins., firmly set, clearly mkd. SC on north, 4 grooves on west and 2 grooves on east, in a collar of stone.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

SC

T40S R25E

S34 | S35

2004

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Bury mkd. stone alongside stainless steel post.

Rebuild reference mound of stone around stainless steel post.

Cor. is located on open flat, 100 ft. north of wash, drains E,
 and 265 ft. north of San Juan County Road No. 417, bears E-W.

N. 89°58.2' E., on the south bdy. of sec. 35.

- 31.847** Point for the 1/4 sec. cor. of sec. 2, at midpoint bet.
 closing cors.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26
 ins. in the ground with magnet at base, with a reference mound
 of stone to the south, with Navajo brass cap mkd.:

T40S

1/4 S2
 T41S R25E
 2004

Cor. is located on gentle and rocky S slope.

- 39.996** Point for the stan. 1/4 sec. cor. of sec. 35, at proportionate
 dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24
 ins. in the ground with magnet at base, in a collar of stone,
 with Navajo brass cap mkd.:

SC
 T40S R25E
 1/4 S35

2004

Cor. is located on small mesa top, near the west edge.

- 71.823** The closing cor. of secs. 1 and 2, T. 41 S., R. 25 E., at
 proportionate dist.; there is no remaining evidence of the
 original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25
 ins. in the ground with magnet at base, in a mound of stone, 3
 ft. base to top, with Navajo brass cap mkd.:

T40S R25E
 S35

 S2 | S1
 CC
 T41S
 2004

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a sandstone ledge, 5 ft. west of east edge of ledge.

- 79.992** The stan. cor. of secs. 35 and 36, monumented with a sandstone, 20X12X6 ins., firmly set, clearly mkd. with 5 grooves on the west face and 1 groove on the east face, in a scattered mound of stone.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

SC	
T40S	R25E
S35	S36

2004

Bury mkd. stone alongside stainless steel post.

Rebuild scattered collar of stone around stainless steel post.

Cor. is located on gentle SE slope, approximately 150 ft. south of rocky outcrop.

N. 88°28.3' E., on the south bdy. of sec. 36.

- 31.952** Point for the 1/4 sec. cor. of sec. 1, at midpoint bet. closing cors.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 2 ft. base, to top, with Navajo brass cap mkd.:

1/4 S1	
T41S	R25E
2004	

Cor. is located on a gradual SW slope, 4 ft. north of a gully, 3 ft. wide, drains W.

- 40.137** Point for the stan. 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 29 ins. in the ground with magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

SC
 T40S R25E
1/4 S36

2004

Cor. is located on a W slope in sand and sagebrush.

- 72.076** Point for the closing cor. of secs. 1 and 6, T. 41 S., Rs. 25 and 26 E., at proportionate dist.; there is no remaining evidence of the original cor. This point is referred to as a tp. cor. in the field notes of the 1899 resurvey record but was mkd. as a closing cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground to solid rock with magnet at base, in mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T40S R24E
S36
 S1 | S6
 R25E R26E
 CC
 T41S
 2004

Cor. is located on a SW slope in sagebrush and scattered grass.

- 80.274** The stan. tp. cor. of Tp. 40 S., Rs. 25 and 26 E., monumented with a sandstone, 16X8X7 ins., loosely set, clearly mkd. SC 40S on north face, 26 E on east face and 25 E on west face, with 6 grooves on the northeast and northwest faces, in a mound of stone. (Record; reference mound of stone to the north)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with magnet at base, with Navajo brass cap mkd.:

SC
 T40S
 R25E R26E
S36 | S31
 2004

Bury mkd. stone alongside stainless steel post.

Rebuild mound of stone to 2 1/2 ft. base, to top, around stainless steel post.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
 (EIGHTH STANDARD PARALLEL SOUTH)
 T. 40 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on a gradual easterly slope, 120 ft. east of a dirt road, 7 ft. wide, bears S. 20° E. and N. 20° W.

Dependent Resurvey of the East Boundary,
 T. 41 S., R. 25 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
 H. D. Page & J. M. Lentz in 1899

From the closing cor. of secs. 1 and 6, T. 41 S., Rs. 25 and 26 E., hereinbefore described.

S. 0°13.2' W., bet. secs. 1 and 6.

- 40.988** Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor., falls within the floodplain of McElmo Creek where it is unsafe to monument.

from which

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd. WC T41S R25E R26E 1/4 S1 S6 2004 and an arrow pointing to the true cor. point, bears N. 50°52.7' W., 0.651 chs. dist. for an offline witness cor.

Cor. is located on northerly bank of McElmo Creek.

- 81.976** The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 20X8X7 ins., loosely set, clearly mkd. with 5 notches on the south and 1 notch on the north edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 27 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S	
R25E R26E	
S1	S6
<hr/>	
S12	S7

2004

Cor. is located on a rocky northerly slope.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 1°39.9' W., bet. secs. 7 and 12.

- 40.184** Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S
R25E R26E
1/4
S12 | S7
2004

Cor. is located on a slight southerly slope in grass and scattered sagebrush.

- 80.368** The cor. of secs. 7, 12, 13 and 18, monumented with a sandstone, 18X10X3 ins., firmly set, clearly mkd. with 4 notches on the south and 2 notches on the north edges, in a collar of stone. (Record; reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S
R25E R26E
S12 | S7
S13 | S18
2004

Bury mkd. stone on west side of stainless steel post.

Cor. is located on a gradual SW slope in scattered grass and sagebrush.

S. 1°38.5' E., bet. secs. 13 and 18.

- 39.888** Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S
R25E R26E
1/4
S13 | S18
2004

Cor. is located on a slight NW slope in scattered sagebrush and grass.

- 79.776** The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone boulder, 10X6X4 ft., clearly mkd. with a + (cross) and 3 notches on the north and south sides of the + (cross), on the NW face of the boulder.

At the corner point

Set a Navajo brass tablet flush with + (cross) on boulder, with brass cap mkd.:

T41S
R25E R26E
S13 | S18
—+—
S24 | S19

2004

Cor. is located approximately 70 ft. N. 80° E. of gravel road, 26 ft. wide, bears S. 10° E. and N. 10° W.

S. 0°00.5' W., bet. secs. 19 and 24.

- 39.956** Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S
R25E R26E
1/4
S24 | S19
2004

Drive a steel fence post alongside stainless steel post.

Cor. is located on a NW slope in grass and scattered sagebrush.

- 79.912** Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with a reference mound of stone to the west, with Navajo brass cap mkd.:

T41S	
R25E	R26E
S24	S19
<hr/>	
S25	S30

2004

Cor. is located on a gentle rolling flat in sparsely scattered juniper.

S. 0°00.5' W., bet. secs. 25 and 30.

- 39.956** The 1/4 sec. cor. of secs. 25 and 30, monumented with a sandstone, 12X10X5 ins., firmly set, dimly mkd. 1/4 on west face, with a reference mound of stone to the west.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	
R25E	R26E
1/4	
S25	S30
2004	

Bury mkd. stone alongside stainless steel post.

Cor. is located on a gentle S. slope.

S. 0°18.9' E., beginning new measurement.

- 39.757** The cor. of secs. 25, 30, 31 and 36, monumented with a sandstone, 16X10X6 ins., firmly set, clearly mkd. with 5 notches on the north and 1 notch on the south edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock with magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S	
R25E	R26E
S25	S30
<hr/>	
S36	S31

2004

Bury mkd. stone alongside stainless steel post.

Cor. is located at base of low ridge, bears N-S, and on gentle E. slope.

S. 0°21.5' W., bet. secs. 31 and 36.

- 40.219** The 1/4 sec. cor. of secs. 31 and 36, monumented with a sandstone, 16X10X7 ins., firmly set, dimly 1/4 S36 on west face, in a mound of stone. (Record; no record of the marks 36 on sandstone, reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	
R25E	R26E
1/4	
S36	S31
2004	

Bury mkd. stone alongside stainless steel post.

Rebuild mound of stone to a collar of stone around stainless steel post.

Cor. is located on flat land, approximately 300 ft. east of dirt road, bears NE-SW, and approximately 300 ft. north of State Highway No. 263 right-of-way fence.

S. 0°13.8' E., beginning new measurement.

- 40.011** Point for the cor. of Tps. 41 and 42 S., Rs. 25 and 26 E., at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with a magnet at base, in a collar of stone, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S	
R25E	R26E
S36	S31
S1	S6
T42S	
2004	

Cor. is located on nearly level rocky terrain.

From this point, the cor. of secs. 4, 5, 32 and 33, Tps. 41 and 42 S., R. 26 E., bears S. $89^{\circ}58.7'$ E., 159.745 chs. dist., monumented with a sandstone, 14X8X5 ins., firmly set, dimly mkd. with 3 notches on the east face, with a reference mound of stone to the north. (Record; 18X8X5 ins., 4 notches on east and 2 notches on west edges, reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 21 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S R26E	
S32	S33
S5	S4
T42S	
2004	

Bury mkd. stone as part of mound of stone around stainless steel post.

Rebuild reference mound of stone to 3 ft. base around stainless steel post.

Cor. is located on SE slope, 30 ft. west of top of spur ridge, bears S. 50° E. and N. 30° W.

From this same point, the 1/4 sec. cor. of secs. 1 and 6, T. 42 S., Rs. 25 and 26 E., bears S. $0^{\circ}22.3'$ W., 40.011 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the 1953 resurvey record.

from which the 1953 reference object

A sloping sandstone boulder, 3X2X1 ft., bears S. 84° W., 13 1/2 lks. dist. to a chiseled 10 ins. cross (X).

Cor. is located on gentle SW rocky slope, at approximate north rim of gulch and south edge of branch, bears S. 70° W. and E.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on gentle SW rocky slope, at approximate north rim of gulch and south edge of branch, bears S. 70° W. and E.

Dependent Resurvey of the South Boundary,
T. 41 S., R. 25 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H. D. Page & J. M. Lentz in 1899

From the cor. of Tps. 41 and 42 S., Rs. 25 and 26 E., hereinbefore described.

N. 89°50.3' W., bet. secs. 1 and 36.

- 39.936** The 1/4 sec. cor. of secs. 1 and 36, monumented with a sandstone, 16X14X6 ins., firmly set, clearly mkd. 1/4 on north face, in a mound of stone. (Record; reference mound of stone to the north)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
S36
1/4 —
S1
T42S
2004

Bury mkd. stone alongside stainless steel post.

Rebuild mound of stone into a collar of stone around stainless steel post.

Cor. is located on open flat, approximately 400 ft. north of water pond.

S. 89°56.5' W., beginning new measurement.

- 39.998** The cor. of secs. 1, 2, 35 and 36, monumented with a sandstone 26X8X6 ins., firmly set, clearly mkd. with 5 notches on the west and 1 notch on the east edges, in a collar of stone. (Record; mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S	R25E
S35	S36
S2	S1
T42S	
2004	

Bury mkd. stone alongside stainless steel post.

Cor. is located on open flat, approximately 150 ft. west of fork in trail road.

S. 89°43.4' W., bet. secs. 2 and 35.

- 40.404** The 1/4 sec. cor. of secs. 2 and 35, monumented with a sandstone, 16X8X6 ins., firmly set, clearly mkd. 1/4 on north face, with a steel fence post alongside.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
S35	
1/4	
S2	
T42S	
2004	

Bury mkd. stone alongside stainless steel post.

Drive steel fence post alongside stainless steel post.

Cor. is located on open flat, approximately 260 ft. north debris basin dam.

S. 89°54.1' W., beginning new measurement.

- 39.996** The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 1 in. above ground, in a mound of stone, with brass cap mkd. as described in the field notes of the 1953 resurvey record.

Cor. is located on a flat bench, 240 ft. east of a fence, bears S. 20° E. and N. 20° W.

Reestablishment of the Resurvey Executed by
A. Nelson & R. G. Yundt in 1953

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°59.4' W., bet. secs. 3 and 34.

- 27.359** The witness meander cor. of secs. 3 and 34, on present day right bank of the San Juan River, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, with brass cap mkd. as described in the field notes of the 1953 resurvey record.

Cor. is located on a flat, 20 ft. east of top of river bank.

S. 89°59.5' W., on continuous measurement.

- 0.650** True point for the 1899 meander cor. of secs. 3 and 34, for the right bank of the San Juan River, falls at base of W. face of the right bank, 20 ft. high, which is eroding, bears NW-SE. This point now functions as an angle point. Not monumented.

Reestablishment of the Survey Executed by
A. Nelson & R. G. Yundt in 1953

S. 89°59.5' W., beginning new measurement.

- 9.701** The witness cor. to the 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 2 1/2 ins. diam., loosely set and leaning, raise iron post to upright position and 25 ins. in the ground, with brass cap mkd.:

S34
WC1/4 ←
S3
1953

This point now functions as the new meander cor. of the right bank of the San Juan River for secs. 3 and 34.


Cor. is located on flat river bottom land.

N. 89°59.0' W., beginning new measurement.

- 2.300** True point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist., falls in unsafe place in dry river bed.
- 5.302** Left bank of the San Juan River, course N. 28° W.; point for the meander cor. of secs. 3 and 34, falls in unsafe place.
- 17.790** Point selected for the witness meander cor. to the meander cor. of secs. 3 and 34, for the left bank of the San Juan River.
- Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS



Cor. is located on flat river bottom.

- 42.307** The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Cor. is located 60 ft. west of westerly edge of a flat, with ledge rock to the east.

N. 89°59.3' W., bet. secs. 4 and 33.

- 40.014** True point for the 1/4 sec. cor. of secs. 4 and 34, at proportionate dist., falls in bottom of wash, drains SE, unsafe to monument.

- 41.064** The witness cor. to the 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a supporting mound of stone, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Witness cor. is located on a flat in scattered sagebrush, 70 ft. west of a wash, drains south.

S. 89°59.8' W., beginning new measurement.

- 38.970** The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Cor. is located on the northerly edge of a draw, 20 ft. north of draw, drains N. 50° E., and 21 ft. west of same draw, drains N. 70° E.

N. 89°59.6' W., bet. secs. 5 and 32.

- 40.024** True point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist., falls in bottom of draw, drains SE, unsafe to monument.

- 43.226** The witness cor. to the 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, 4 ft.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

base, to top, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Witness cor. is located on top of a low rise.

N. 89°58.6' W., beginning new measurement.

- 36.804** The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, in a mound of stone, 4 ft. base to top, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Cor. is located on steep W. slope in scattered scrub oak and sagebrush.

S. 89°59.6' W., bet. secs. 6 and 31.

- 39.870** The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Cor. is located on a small flat area in cactus, grass and sagebrush.

N. 89°58.5' W., beginning new measurement.

- 37.311** The cor. of Tps. 41 and 42 S., R. 25 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with reference mound of stone to the north, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Cor. is located 25 ft. east of a wash, drains N. 10° E., 35 ft. west of center of dirt road, 10 ft. wide, bears N. 20° E. and S.

Dependent Resurvey of the West Boundary,
T. 41 S., R. 25 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H. D. Page & J. M. Lentz in 1899

From the point for the closing cor. of secs. 1 and 6, T. 41 S., Rs. 24 and 25 E., hereinbefore described.

S. 0°11.2' W., bet. secs. 1 and 6.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.002 The 1/4 sec. cor. of secs. 1 and 6, monumented with a sandstone, 22X12X6 ins., firmly set, in a mound of stone, dimly mkd. 1/4 on west face. (Record; reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground with magnet at base, in a mound of stone, 4 ft. base, to top, with brass cap mkd.:

T41S
R24E R25E
1/4
S6 | S1
2004

Bury dimly mkd. stone alongside stainless steel post.

Rebuild original mound of stone around stainless steel post.

Cor. is located on gentle NW slope.

S. 0°05.4' E., beginning new measurement.

39.847 The cor. of secs. 1, 6, 7 and 12, monumented with a sandstone, 12X10X8 ins., loosely set, clearly mkd. with 5 notches on the south and 1 notch on the north edges, with a reference mound of stone to the west. (Record; 16X10X4 ins., in a mound of stone)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.:

T41S
R24E R25E
S1 | S6

S12 | S7
2004

Bury mkd. stone on north side of stainless steel post.

Rebuild reference mound of stone around stainless steel post.

Cor. is located on top of a spur ridge, bears S. 50° E. and N. 50° W.

S. 0°01.3' W., bet. secs. 7 and 12.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.077 The 1/4 sec. cor. of secs. 7 and 12, monumented with a sandstone, 16X10X6 ins., firmly set, clearly mkd. 1/4 on west face, in a mound of stone.

Note: The 1953 resurvey record indicates that an iron post was set at the point for the cor., the mkd. stone was buried, and broken glass was placed at the base of the iron post. No remains of the 1953 iron post was recovered. The mkd. stone, in a mound of stone is accepted as the best available evidence of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S
R24E R25E
1/4
S12|S7
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on top of a small spur ridge, sloping SE, and approximately 515 ft. north of State Highway No. 262, bears E-W.

Reestablishment of the Resurvey Executed by
A. Nelson & R. G. Yundt in 1953

S. 0°00.8' E., beginning new measurement.

40.010 Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the 1953 iron post.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S
R24E R25E
S12 | S7

S13 | S18
2004

Drive a steel fence post 0.8 ft. west of stainless steel post.

Cor. is located in sand on a river flood plain.


DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 0°00.8' E., bet. secs. 13 and 18.

- 4.838** Point selected for the witness cor. to the meander cor. for secs. 13 and 18, right bank of the San Juan River.


Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:



Witness cor. is located in sand and tamarisk.

- 4.965** True point right bank of San Juan River, course N. 74° W.; point for meander cor. for secs. 13 and 18, falls at base of river bank which is subject to destruction.
- 10.339** True point for left bank of San Juan River; point for the meander cor. of secs. 13 and 18, falls at base of river bank which is subject to destruction.
- 16.905** Point selected for the witness cor. to the meander cor. for secs. 13 and 18, left bank of the San Juan River.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:



Witness cor. is located 20 ft. north of dirt road, 20 ft. wide, bears E-W.

- 24.306** The original meander cor. of secs. 13 and 18, right bank of the San Juan River, monumented with an iron post, 2 1/2 ins. diam., firmly set, 5 ins. below ground, with brass cap mkd. as described in the field notes of the 1953 resurvey record.

This point now functions as an angle point.

Remove the marks MC from the brass cap.

Add the marks AP 2004 to brass cap.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Brass cap is now mkd.:

T41S	
R24E R25E	
S13	S18
AP	
1953	
2004	

Cor. is located on sandy and level river bottom in short tamarisk and willow.

Reestablishment of the Survey Executed by
A. Nelson & R. G. Yundt in 1953

S. 0°00.1' W., beginning new measurement.

- 15.708** The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. as described in the field notes of the 1953 original survey record.

Cor. is located on level sandy river bottom in short tamarisk and willow.

S. 0°02.3' W., beginning new measurement.

- 40.022** The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., firmly set, in a mound of stone with brass cap mkd. as described in the field notes of the 1953 original survey record.

from which the original bearing object

A sandstone bedrock, bears S. 74 1/2° E., 75 1/2 lks. dist., to a chiseled 12 ins. cross "X".

Cor. is located on a gradual SE. slope in scattered sagebrush.

S. 0°00.7' E., bet. secs. 19 and 24.

- 40.011** The 1/4 sec. cor. of secs. 19 and 24, monumented with a chiseled "X" on a boulder and remains of a partial mound of stone, and is accepted as the best available evidence of the original cor.

Note: This point falls on ledge boulder. There has been a mud slide in the area. The 1953 iron post was not recovered.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point drive a PK-nail flush with center of
chiseled "X".

from which the new reference object

A ledge boulder, bears N. 52°31.6' E., 12.7 lks. dist.
to a 10 ins. chiseled "X".

Cor. is located on ledge boulder.

S. 0°01.1' W., beginning new measurement.

- 40.011** Point for the cor. of secs. 19, 24, 25 and 30, at
proportionate dist.; there is no remaining evidence of the
original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28
ins. in the ground with magnet at base, with brass cap mkd.:

T41S	
R24E	R25E
S24	S19
<hr/>	
S25	S30

2004

Drive a steel fence post along north side of stainless steel
post.

Cor. is located on the westerly edge of the top of a sand
dune.

S. 0°01.1' W., bet. secs. 25 and 30.

- 34.009** The witness cor. to the 1/4 sec. cor. of secs. 25 and 30,
monumented with an iron post, 2 1/2 ins. diam., firmly set, 24
ins. below sand dune surface, with brass cap mkd. as described
in the field notes of the 1953 original survey record.

Drive a steel fence post along east side of iron post.

Cor. is located in a sand dune.

South, beginning new measurement.

- 6.004** True point for the 1/4 sec. cor. of secs. 25 and 30, at
proportionate dist., falls in wash, unsafe to monument.

- 46.031** The cor. of secs. 25, 30, 31 and 36, determined at record
bearing and dist. from the original bearing object

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

A sandstone boulder, 4X4X1 ft., bears N. 35°25' E.,
1.24 chs. dist. to a chiseled "X".

Note: No remaining evidence of the original iron post was
recovered.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26
ins. in the ground with magnet at base, with Navajo brass cap
mkd.:

T41S	
R24E	R25E
S25	S30
<hr/>	
S36	S31

2004

Drive a steel fence post along northeast side of stainless
steel post.

Cor. is located on a NW slope in sand dune, and 6 ft. east of
a draw, drains N. 10° E.

S. 0°00.6' E., bet. secs. 31 and 36.

40.002 True point for the 1/4 sec. cor. of secs. 31 and 36, at
proportionate dist.; there is no remaining evidence of the
original cor., falls in main wash of canyon, unsafe to
monument.

41.002 The witness cor. to the 1/4 sec. cor. of secs. 31 and 36,
monumented with an iron post, 2 1/2 ins. diam., firmly set,
projecting 8 ins. above ground, in a mound of stone, with
brass cap mkd. as described in the field notes of the 1953
original survey record.

Cor. is located in desert flora.

S. 0°00.9' W., beginning new measurement.

29.450 The cor. of Tps. 41 and 42 S., R. 24 E., monumented with an
iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins.
above ground, with brass cap mkd. as described in the field
notes of the 1953 original survey record, from which a
reference mound of stone, bears west, 10.5 lks. dist. to the
center of the mound.

Cor. is located 24 ft. east of a wash, drains N. 10° E., and 17
ft. west of the center of dirt road, 20 ft. wide, bears
N. 30° E. and S.

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

S. 0°01.8' E., bet. secs. 1 and 31, beginning new measurement.

- 9.730** The cor. of Tps. 41 and 42 S., R. 25 E., hereinbefore described.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 41 S., R. 25 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
H. D. Page & J. M. Lentz in 1899

From the cor. of secs. 1, 2, 35 and 36, on the south bdy. of the tp., hereinbefore described.

N. 0°06.4' W., bet. secs. 35 and 36.

- 39.951** The 1/4 sec. cor. of secs. 35 and 36, monumented with a sandstone, 16X10X4 ins., clearly mkd. 1/4 on west face, in a mound of stone. (Record; reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with magnet at base, with Navajo brass cap mkd.:

T41S R25E
1/4
S35 | S36
2004

Bury mkd. stone on north side of stainless steel post.

Rebuild mound of stone to 3 ft. base, around stainless steel post.

Cor. is located on NE slope in scattered juniper, 55 ft. S. 50° W., of a draw, drains N. 30° W.

N. 0°08.3' W., beginning new measurement.

- 39.808** The cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 16X10X3 ins., firmly set, clearly mkd. with one notch on the south and east edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

T41S	R25E
S26	S25
S35	S36

2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on steep E slope, approximately 70 ft. above bottom of wash.

From the cor. of secs. 25, 30, 31 and 36, on the east bdy. of the tp., hereinbefore described.

S. 89°43.0' W., bet. secs. 25 and 36.

- 40.091** Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with a reference mound of stone, 3 ft. base, to the north, with a Navajo brass cap mkd.:

T41S	R25E
	S25
1/4	—
	S36
	2004

Cor. is located on a SW slope in sagebrush and scattered juniper, 25 ft. N. 45° E. of a draw, drains N. 20° W.

- 80.182** The cor. of secs. 25, 26, 35 and 36.

N. 0°08.2' W., bet. secs. 25 and 26.

- 40.022** Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock with a magnet at base, in a supporting mound of stone, 4 ft. base to top, with Navajo brass cap mkd.:

T41S	R25E
	1/4
S26	S25
	2004

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on rocky NW slope, approximately 130 ft. below ridge top, on west side of ridge.

- 80.044** Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	R25E
S23	S24
S26	S25

2004

Cor. is located on north sandy slope, 10 ft. south of wash, drains west, and 25 ft. north of water pipe line.

From the cor. of secs. 19, 24, 25 and 30, on the east bdy. of the tp., hereinbefore described.

S. 89°54.5' W., bet. secs. 24 and 25.

- 40.146** The 1/4 sec. cor. of secs. 24 and 25, monumented with a sandstone, 20X10X4 ins., loosely set and leaning, dimly mkd. 1/ on one side. Place mkd. stone in an upright position to measure to.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a supporting mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S	R25E
	S24
1/4	—————
	S25
	2004

Bury mkd. stone along SW side of aluminum post.

Cor. is located on a northerly slope in sharp cactus, 55 ft. north of center of power line, bears E-W.

S. 89°59.7' W., beginning new measurement.

- 39.998** The cor. of secs. 23, 24, 25 and 26.

N. 0°04.0' E., bet. secs. 23 and 24.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.021 The 1/4 sec. cor. of secs. 23 and 24, monumented with a sandstone, 16X12X6 ins., firmly set, clearly mkd. 1/4 on west face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
1/4
S23 | S24
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on NE slope of low spur, 75 ft. east of gravel road, bears N-S, 30 ft. south of small draw, drains NW.

N. 0°04.6' W., beginning new measurement.

39.936 The cor. of secs. 13, 14, 23 and 24, monumented with a sandstone, 14X14X8 ins., firmly set, clearly mkd. with 3 notches on the south and 1 notch on the east edges, with a reference mound of stone to the west.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground with magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
S14 | S13
—+—
S23 | S24
2004

Bury mkd. stone alongside stainless steel post.

Rebuild reference mound of stone around stainless steel post.

Cor. is located on a rocky E slope, approximately 530 ft. west of gravel road, bears N-S.

From the cor. of secs. 13, 18, 19 and 24, on the east bdy. of the tp., hereinbefore described.

N. 89°58.4' W., bet. secs. 13 and 24.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.932 The 1/4 sec. cor. of secs. 13 and 24, monumented with a sandstone, 18X12X8 ins., firmly set, clearly mkd. 1/4 on north face, with a reference mound of stone to the north.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
S13
1/4 ———
S24
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on a rocky NW slope.

S. 89°56.4' W., beginning new measurement.

39.217 The cor. of secs. 13, 14, 23 and 24.

N. 0°28.5' E., bet. secs. 13 and 14.

39.330 The 1/4 sec. cor. of secs. 13 and 14, monumented with a sandstone, 24X12X6 ins., firmly set, clearly mkd. 1/4 on west face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
1/4
S14 | S13
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on open flat, 30 ft. west of dirt road.

N. 0°28.6' W., beginning new measurement.

40.777 The cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 20X12X4 ins., firmly set, clearly mkd. with 4 notches on the south and 1 notch on the east edges.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
S11	S12
S14	S13

2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on open flat, and on N edge of dirt road.

From the cor. of secs. 7, 12, 13 and 18, on the east bdy. of the tp., hereinbefore described.

N. 89°30.1' W., bet. secs. 12 and 13.

- 37.714** The 1/4 sec. cor. of secs. 12 and 13, monumented with a sand stone, 18X14X4 ins., loosely set, clearly mkd. 1/4 on north face, with a reference mound of stone to the north.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S	R25E
S12	
1/4	—
S13	
2004	

Bury mkd. stone, marks down, as part of mound of stone.

Rebuild reference mound of stone around stainless steel post.

Cor. is located on a west slope, in scattered desert brush, 60 ft. east of a draw, drains N. 30° E.

N. 89°59.3' W., beginning new measurement.

- 40.149** The cor. of secs. 11, 12, 13 and 14.

N. 0°03.5' E., bet. secs. 11 and 12.

- 40.052** The 1/4 sec. cor. of secs. 11 and 12, monumented with a sandstone, 16X10X4 ins., firmly set, clearly mkd. 1/4 on west

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

face, in a collar of stone. (Record; reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
1/4
S11 | S12
2004

Bury mkd. stone alongside stainless steel post.

Rebuild collar of stone around stainless steel post.

Cor. is located on gentle NW slope, approximately 50 ft. south of dirt road.

N. 0°56.9' E., beginning new measurement.

39.649 The cor. of secs. 1, 2, 11 and 12, monumented with a sandstone, 16X10X8 ins., clearly mkd. with 5 notches on the south and 1 notch on the east edges, in a mound of stone, with a reference mound of stone, 10 1/2 lks. to the west.

At the corner point

Set a stainless steel post, 30 ins. long, 14 ins. in the ground to solid rock with magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
S2 | S1
S11 | S12
2004

Bury mkd. stone along west side of stainless steel post.

Rebuild reference mound of stone around stainless steel post.

Cor. is located on a spur ridge, bears N-S.

From the cor. of secs. 1, 6, 7 and 12, on the east bdy. of the tp., hereinbefore described.

S. 89°47.0' W., bet. secs. 1 and 12.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.742** The true point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor., falls within the flood plain of McElmo Creek, where it is subject to destruction.

from which

The point selected for the offline witness cor. to the 1/4 sec. cor. of secs. 1 and 12, bears N. 65°28.6' W., 5.058 chs. dist., to a stainless steel post, 31 ins. long, 2 1/2 ins. diam., 27 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

WC
T41S R25E
S1
1/4 →
S12
2004

Note: No suitable location for an online witness cor. to the east or west of the true point within limits could be located.

Witness cor. is located on a gradual SE slope.

- 78.484** The cor. of secs. 1, 2, 11 and 12.

N. 0°18.6' W., bet. secs. 1 and 2.

- 40.178** Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to solid rock with magnet at base, in a mound of stone, 2 ft. base, with Navajo brass cap mkd.:

T41S R25E
1/4
S2 | S1
2004

from which the reference object

A power pole, 14 ins. diam., bears N. 22°18.0' W., 103.2 lks. dist. to a nail and metal tag mkd. PC NWP N10-94 DF45 4-40.

Cor. is located on a slight SE slope in scattered grass and weeds.

- 80.356** The closing cor. of secs. 1 and 2, hereinbefore described.
-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 2, 3, 34 and 35, on the south bdy. of the tp., hereinbefore described.

N. 0°01.7' W., bet. secs. 34 and 35.

- 40.007** Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E	
1/4	
S34	S35
2004	

Cor. is located on a flat in an abandoned farm field.

- 80.014** Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist., utilizing three-point control; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E	
S27	S26
<hr/>	
S34	S35

2004

Cor. is located in an abandoned farm field, 240 ft. south of a fence, bears S. 70° E. and N. 70° W.

From the cor. of secs. 25, 26, 35 and 36.

N. 89°54.4' W., bet. secs. 26 and 35.

- 40.255** The 1/4 sec. cor. of secs. 26 and 35, monumented with a cobblestone, 18X10X4 ins., firmly set, clearly mkd. 1/4 on north face, with a scattered reference mound of stone to the north.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R25E
S26
1/4 ———
S35
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on S slope into canyon, drains W.

S. 89°53.8' W., beginning new measurement.

40.000 The cor. of secs. 26, 27, 34 and 35.

West, bet. secs. 27 and 34.

40.000 Point for the 1/4 sec. cor. of secs. 27 and 34, at record bearing and dist. from the cor. of secs. 26, 27, 34 and 35; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.

T41S R25E
S27
1/4 ———
S34
2004

Cor. is located on a slight easterly slope in grass.

49.000 Point for the 1899 meander cor. of secs. 27 and 34, at record bearing and dist. from the cor. of secs. 26, 27, 34 and 35; there is no remaining evidence of the original cor., falls in San Juan River flood plain, now functions as an angle point.

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
A S27
P S34
2004

Cor. is located within the flood plain of the current San Juan River.

From the cor. of secs. 26, 27, 34 and 35.

N. 0°02.5' E., bet. secs. 26 and 27.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 40.008** The 1/4 sec. cor. of secs. 26 and 27, monumented with an unrecorded iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, with a cobblestone, 14X10X6 ins., clearly mkd. 1/4 on one side. The marked stone has been disturbed. The iron pipe is accepted as a faithful and careful perpetuation of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, with Navajo brass cap mkd.:

T41S R25E
1/4
S27 | S26
2004

Bury iron pipe and mkd. stone alongside stainless steel post.

Rebuild mound of stone around stainless steel post.

Cor. is located on a gradual northerly slope in scattered sagebrush.

N. 0°00.2' E., beginning new measurement.

- 10.008** Point for the S-N 1/64 sec. cor. of secs. 26 and 27. Not monumented.
- 15.012** Point for the N-S-N 1/256 sec. cor. of secs. 26 and 27. Not monumented.
- 20.016** Point for the N 1/16 sec. cor. of secs. 26 and 27.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

N 1/16
S27 | S26
2004

Drive a steel fence post alongside stainless steel post.

Cor. is located in scattered sagebrush.

- 25.020** Point for the S-N-N 1/256 sec. cor. of secs. 26 and 27.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS


S-N-N 1/256
S27 | S26
2004

Drive a steel fence post alongside stainless steel post.

Cor. is located 3.5 ft. east of easterly edge of dirt road.

- 28.551** Point for Angle Point Number 8, Tract 37, at intersection with the westerly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 51°13.5' E. and N. 51°13.5' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:



2004

Cor. is located on a small flat area in sand.

- 29.134** Intersect the centerline of Texas-New Mexico Pipeline Company oil pipe line, bears S. 51°13.5' E. and N. 51°13.5' W.
- 29.717** Intersect the easterly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 51°13.5' E. and N. 51°13.5' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file.
- 30.024** Point for the N-N 1/64 sec. cor. of secs. 26 and 27. Not monumented.
- 40.032** The cor. of secs. 22, 23, 26 and 27, monumented with an unrecorded rebar, 1/2 in. diam., firmly set, 14 ins. below ground, with a cobblestone, 14X10X6 ins., clearly mkd. with 2 grooves on 2 sides, along south side of rebar, in a mound of stone. The rebar is accepted as a faithful and careful perpetuation of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

T41S	R25E
S22	S23
S27	S26

2004

Bury rebar inside stainless steel post.

Bury mkd. stone along west side of stainless steel post.

Rebuild mound of stone to 2 ft. base around stainless steel post.

from which the unrecorded reference objects

An iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, bears N. 0°06.0' W., 74.7 lks. dist.

An iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, bears S. 89°05.5' E., 75.6 lks. dist.

An iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, bears S. 0°18.0' W., 76.6 lks. dist.

An iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, bears N. 89°44.7' W., 75.9 lks. dist.

Cor. is located 6 ft. south of draw, drains NW.

From the cor. of secs. 23, 24, 25 and 26.

S. 89°59.4' W., bet. secs. 23 and 26.

40.008 Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
S23	
1/4	—
S26	
2004	

Cor. is located in driveway, near 3 homes.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

80.016 The cor. of secs. 22, 23, 26 and 27.

N. 0°05.4' W., bet. secs. 22 and 23.

39.971 The 1/4 sec. cor. of secs. 22 and 23, monumented with a sandstone, 12X8X4 ins., loosely set, dimly mkd. 1/4 on west face. (Record; 14X8X6 ins., reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E	
1/4	
S22	S23
2004	

Bury mkd. stone alongside stainless steel post.

Cor. is located on a very gradual west slope, approximately 60 ft. east of a dirt road, 9 ft. wide, bears N-S.

N. 0°03.7' E., beginning new measurement.

40.165 The cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 24X18X18 ins., firmly set, clearly mkd. with 3 notches on the south and 2 notches on the east edges, in a mound of stone, with a reference mound of stone to the west.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to solid rock with a magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E	
S15	S14
<hr/>	
S22	S23

2004

Bury mkd. stone on west side of stainless steel post as part of the mound of stone.

Rebuild mound of stone and reference mound of stone around stainless steel post.

Cor. is located on a S slope in a slide rock area.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

From the cor. of secs. 13, 14, 23 and 24.

N. 89°53.2' W., bet. secs. 14 and 23.

- 40.076** The 1/4 sec. cor. of secs. 14 and 23, monumented with a sandstone, 14X12X8 ins., loosely set, clearly mkd. 1/4 on north face. (Record; reference mound of stone to the north)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base to top, with Navajo brass cap mkd.:

T41S R25E
S14
1/4 ———
S23
2004

Bury mkd. stone on west side of stainless steel post.

Cor. is located on a westerly slope in rock, 30 ft. west of dirt road, 7 ft. wide, bears N-S.

N. 89°52.7' W., beginning new measurement.

- 39.937** The cor. of secs. 14, 15, 22 and 23.

N. 0°01.2' W., bet. secs. 14 and 15.

- 39.967** Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionated dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
1/4
S15 | S14
2004

Cor. is located 125 ft. S. 80° E. of a dirt road, 12 ft. wide, bears N. 20° E. and S. 20° W., 25 ft. S. 80° E. of a 2-wire power line, bears N. 30° E. and S. 30° W.

- 79.934** The cor. of secs. 10, 11, 14 and 15, monumented with a sandrock, 18X10X5 ins., firmly set, clearly mkd. with 4 notches on the south and 2 notches on the east edges, with an unrecorded rebar, 5/8 in. diam., 18 ins. long, alongside, in a collar of stone.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a collar of stone, 1 1/2 ft. base, with Navajo brass cap mkd.:

T41S	R25E
S10	S11
S15	S14

2004

Bury mkd. stone alongside stainless steel post.

Bury rebar inside stainless steel post.

Cor. is located on the northerly end of a flat in grass.

From the cor. of secs. 11, 12, 13 and 14.

S. 89°59.7' W., bet. secs. 11 and 14.

- 40.006** Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S	R25E
S11	
1/4	—
S14	
2004	

Cor. is located on a gradual SW slope in grass.

- 80.012** The cor. of secs. 10, 11, 14 and 15.
-

N. 0°24.5' E., bet. secs. 10 and 11.

- 39.970** Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R25E
1/4
S10 | S11
2004

Cor. is located on nearly level land, approximately 30 ft. north of dirt road, bears E-W.

- 79.940** Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
S3 | S2

S10 | S11
2004

From this point, a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.: NAVAJO LAND DEVELOPMENT, bears S. 76°19.7' W., 0.260 chs. dist., set using incorrect procedures and is not utilized during the course of this resurvey. The Navajo Survey Department was contacted in Window Rock, New Mexico. The Navajo Survey Department said that if the brass cap did not have any marks for being a sec. cor., then the point was used as a control point and not a sec. cor.

Cor. is located on nearly level mesa top.

From the cor. of secs. 1, 2, 11 and 12.

N. 89°50.0' W., bet. secs. 2 and 11.

- 40.062** Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
S2
1/4-----
S11
2004

Cor. is located on gentle NE slope, 25 ft. south of old bulldozed road.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

80.124 The cor. of secs. 2, 3, 10 and 11.

N. 0°13.0' W., bet. secs. 2 and 3.

39.967 The 1/4 sec. cor. of secs. 2 and 3, monumented with a sandstone, 20X8X6 ins., firmly set, clearly mkd. 1/4 on west face, in a mound of stone. (Record; reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E

1/4

S3 | S2

2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on a slight northeasterly slope in scattered sagebrush, 40 ft. south of dirt road, 7 ft. wide, bears N. 70° E. and S. 70° W.

N. 0°11.0' W., beginning new measurement.

39.975 The closing cor. of secs. 2 and 3, monumented with a sandstone, 14X12X4 ins., firmly set, clearly mkd. CC on the south, 4 grooves on the south and 2 grooves on the east edges, with an unrecorded rebar, 1/2 in. diam., firmly set, projecting 3 ins. above ground, along west side of mkd. stone, with a reference mound of stone to the west.

Add the marks AM to mkd. stone and bury in place.

Bury rebar alongside AM stone.

Move reference mound of stone to closing cor. at intersection with the south bdy. of T. 40 S., R. 25 E., Eighth Standard Parallel South, around stainless steel post.

40.114 Point for the closing cor. of secs. 2 and 3, at intersection with the south bdy. of T. 40 S., R. 25 E., Eighth Standard Parallel South.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 2 1/2 ft. base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

T40S R25E
S34
—
S3 | S2
CC
T41S
2004

Cor. is located on a gradual SE slope in grass.

Dependent Resurvey of Auxiliary Base Line, between
sections 7, 8, 9, 10 and 15, 16, 17, and 18,
T.41 S., R.25 E., Salt Lake Meridian, Utah.

Note: T. 41 S., R. 25 E., S.L.M., Ut. surveyed by H. D. Page & J. M. Lentz in 1899 is a fractional tp. because of the San Juan River. Only a portion of the subdivisional and meander lines were surveyed by H. D. Page & J. M. Lentz in 1899. A auxiliary base line was surveyed on a random line from the cor. of secs. 10, 11, 14 and 15 to the cor. of secs. 7, 12, 13 and 18, on the west bdy. of the tp. The direction of the true auxiliary base line is returned as running from the cor. of secs. 7, 12, 13 and 18, on the west bdy. of the tp. to the cor. of secs. 10, 11, 14 and 15. The remaining field notes and plat for this resurvey will follow the same order as the 1899 survey executed by H. D. Page & J. M. Lentz did. The decision was made that this was the best order in which to write the field notes so that the direction of the lines resurveyed in the 2004 resurvey and the 1899 original survey were in the same direction.

From the cor. of secs. 7, 12, 13 and 18, on the west bdy. of the tp., hereinbefore described.

S. 89°54.2' E., bet. secs. 7 and 18, along auxiliary base line.

37.668 The 1/4 sec. cor. of secs. 7 and 18, monumented with a cobblestone, 18X6X5 ins., clearly mkd. 1/4 on north face, in a collar of stone. (Record; reference mound of stone to the north)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
S7
1/4 —
S18
2004

DEPENDENT RESURVEY OF AUXILIARY BASE LINE, BETWEEN
SECTIONS 7, 8, 9, 10 AND 15, 16, 17 AND 18,
T.41 S., R.25 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

Bury mkd. stone on east side of stainless steel post.

Rebuild collar of stone around stainless steel post.

Cor. is located on a gradual SW slope.

N. 89°59.3' E., along auxiliary base line, beginning new measurement.

- 39.998** Point for the cor. of secs. 7, 8, 17 and 18, at single proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	R25E
S7	S8
S18	S17

2004

Cor. is located on a small flat area in scattered sagebrush.

N. 89°59.3' E., bet. secs. 8 and 17, along auxiliary base line.

- 39.998** Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S	R25E
S8	
1/4	—
S17	
2004	

Cor. is located on a gradual west slope in rock, 80 ft. west of top of spur ridge, bears south and N. 40° W.

- 79.996** Point for the cor. of secs. 8, 9, 16 and 17, monumented with a sandstone, 18X8X6 ins., firmly set, dimly mkd. with 4 notches on the south and 3 notches on the east edges, with an unrecorded rebar, 1/2 in. diam., firmly set, alongside mkd. stone, in a mound of stone.

DEPENDENT RESURVEY OF AUXILIARY BASE LINE, BETWEEN
 SECTIONS 7, 8, 9, 10 AND 15, 16, 17 AND 18,
 T.41 S., R.25 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	R25E
S8	S9
S17	S16

2004

Deposit mkd. stone alongside stainless steel post.

Bury rebar inside stainless steel post.

Cor. is located on gentle N slope, approximately 150 ft. south of north rim of mesa top.

S. 89°56.2' E., bet. secs. 9 and 16, along auxiliary base line.

39.817 Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	R25E
S9	
1/4	
S16	
2004	

Cor. is located on a low flat mesa top, approximately 33 ft. north of wash, drains east.

79.634 Point for the cor. of secs. 9, 10, 15 and 16, at single proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
S9	S10
S16	S15

2004

DEPENDENT RESURVEY OF AUXILIARY BASE LINE, BETWEEN
 SECTIONS 7, 8, 9, 10 AND 15, 16, 17 AND 18,
 T.41 S., R.25 E., SALT LAKE MERIDIAN, UTAH.

CHAINS

S. 89°56.2' E., bet. secs. 10 and 15, along auxiliary base line.

- 39.817** Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
 S10
 1/4 ———
 S15
 2004

- 79.634** The cor. of secs. 10, 11, 14 and 15.

Dependent Resurvey of a Portion of the Subdivisional Lines,
 T. 41 S., R. 25 E., Salt Lake Meridian, Utah

Reestablishment of the Survey Executed by
 H. D. Page & J. M. Lentz in 1899

From the cor. of secs. 9, 10, 15 and 16, on the auxiliary base line.

S. 0°35.0' W., bet. secs. 15 and 16.

- 39.875** The 1/4 sec. cor. of secs. 15 and 16, falls on ledge rock, monumented with a chiseled "+" and chiseled 1/4 in northwest quadrant of chiseled "+", with a reference mound of stone, 2 1/2 ft. base, west, 3 lks. dist. to center of mound of stone. (Record; sandrock, 10X10X6 ins., 1/4 S on west.)

from which

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., projecting 6 ins. above ground, for a reference monument, bears S. 41°18.9' E., 37.9 lks. dist., with Navajo brass cap mkd. RM T41S R25E 1/4 S15 2004 and an arrow pointing to the true cor.

Cor. is located on SE slope in ledge rock, 20 ft. north of draw, drains N. 30° E.

S. 0°02.0' E., beginning new measurement.

- 40.000** Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist., utilizing 3-point control; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	R25E
S16	S15
S21	S22

2004

Cor. is located on gentle S slope, 130 ft. south of mesa rim.

From the cor. of secs. 14, 15, 22 and 23.

N. 89°53.6' W., bet. secs. 15 and 22.

- 40.030** Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S	R25E
S15	
1/4	—
S22	
2004	

Cor. is located on gentle E slope, near sparsely scattered juniper trees.

- 80.060** The cor. of secs. 15, 16, 21 and 22.

S. 0°04.9' E., bet. secs. 21 and 22.

- 40.000** Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
1/4	
S21	S22
2004	

Cor. is located on gentle N slope of sand dune, approximately 330 ft. NE of tan colored house and gray colored house.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 68.416 Right bank of San Juan River, course N. 57° W.; point for the meander cor. of secs. 21 and 22. Not monumented.
- 71.125 Left bank of San Juan River; point for the meander cor. of secs. 21 and 22. Not monumented.
- 77.375 Left bank of San Juan River, course N. 45° E.; point for the meander cor. of secs. 21 and 22. Not monumented.
- 79.547 Right bank of San Juan River; point for the meander cor. of secs. 21 and 22. Not monumented.
- 80.000 True point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist., utilizing 2-point control; there is no remaining evidence of the original cor., falls within the banks of the San Juan River, unsafe to monument.

From the cor. of secs. 22, 23, 26 and 27.


N. 89°33.5' W., bet. secs. 22 and 27.

- 9.996 Point for the E-E 1/64 sec. cor. of secs. 22 and 27. Not monumented.
- 13.126 Intersect the easterly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 59°01.3' E. and N. 59°01.3' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file.
- 14.021 Intersect the centerline of Texas-New Mexico Pipeline Company oil pipe line, bears S. 59°01.3' E. and N. 59°01.3' W.
- 14.916 Point for Angle Point Number 1, of Tract 37, at intersection with the westerly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 59°01.3' E. and N. 59°01.3' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS



Cor. is located on SW slope in gravel.

- 19.992** Point for the E 1/16 sec. cor. of secs. 22 and 27. Not monumented.
- 39.984** The 1/4 sec. cor. of secs. 22 and 27, monumented with a cobble rock, 12X10X6 ins., firmly set, clearly mkd. 1/4 on north face, in a mound of stone. (Record; reference mound of stone to the north)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
S22
1/4 ———
S27
2004

Bury mkd. stone along NW side of aluminum post.

Cor. is located on a slight northwesterly slope.

S. 89°57.9' W., beginning new measurement.

- 36.107** Point selected for the witness cor. to the cor. of secs. 21, 22, 27 and 28.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

WC
T41S R25E
S21 | S22
←———
S28 | S27
2004

- 40.000** True point for the cor. of secs. 21, 22, 27 and 28.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the cor. of secs. 9, 10, 15 and 16, on the auxiliary base line.

N. 0°04.5' E., bet. secs. 9 and 10.

- 39.939** Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. base to top, with Navajo brass cap mkd.:

T41S R25E
1/4
S9 | S10
2004

Cor. is located on SW slope of small spur, slopes S.

- 79.878** The cor. of secs. 3, 4, 9 and 10, monumented with a sandstone, 16X8X8 ins., firmly set, clearly mkd. with 5 notches on the south and dimly mkd. with 3 notches on the east edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock with magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
S4 | S3

S9 | S10
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on a brush covered N slope.

From the cor. of secs. 2, 3, 10 and 11.

N. 89°58.7' W., bet. secs. 3 and 10.

- 40.042** True point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor., falls on steep and ledgy S slope, unsafe to monument.

- 43.994** Point selected for the witness cor. to the 1/4 sec. cor. of secs. 3 and 10.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
S3
1/4 → W
S10 C
2004

Witness cor. is located on E slope, approximately 20 ft. west of ledge, bears N-S.

80.084 The cor. of secs. 3, 4, 9 and 10.

N. 0°02.9' E., bet. secs. 3 and 4.

40.092 The 1/4 sec. cor. of secs. 3 and 4, monumented with a sandstone, 18X8X8 ins., firmly set, clearly mkd. 1/4 on west face, in a mound of stone, 3 ft. base.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock with magnet at base, in a mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
1/4
S4 | S3
2004

Bury mkd. stone, mkd. side down, as part of mound of stone.

Rebuild mound of stone to 3 ft. base around stainless steel post.

Cor. is located on a stone ledge, 15 ft. high.

N. 0°19.9' W., beginning new measurement.

39.896 The closing cor. of secs. 3 and 4, T. 41 S., R. 25 E., monumented with a sandstone, 16X10X8 ins., firmly set, clearly mkd. with 3 notches on the east and west edges, and CC on the south face, with a reference mound of stone to the south. (Record; 3 grooves on the east and west faces)

Add the marks AM to mkd. stone and bury in place.

Rebuild reference mound of stone around stainless steel post for the closing cor. of secs. 3 and 4, at the intersection with the south bdy. of T. 40 S., R. 25 E., Eighth Standard Parallel South.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 39.950** Point for the closing cor. of secs. 3 and 4, at intersection with the south bdy. of T. 40 S., R. 25 E., Eighth Standard Parallel South, hereinbefore described.

From the cor. of secs. 8, 9, 16 and 17, on the auxiliary base line.

S. 1°06.8' W., bet. secs. 16 and 17.

- 39.464** The 1/4 sec. cor. of secs. 16 and 17, monumented with a sandstone, 16X10X4 ins., firmly set, clearly mkd. 1/4 on west face, with an unrecorded rebar, 5/8 in. diam., firmly set along east side of mkd. stone, with a reference mound of stone to the east. (Record; reference mound of stone to the west)

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
1/4	
S17	S16
2004	

Bury mkd. stone along west side of stainless steel post.

Bury rebar inside stainless steel post.

Rebuild reference mound of stone to 3 ft. base around stainless steel post.

Cor. is located on a SW slope in scattered sagebrush.

S. 0°00.3' E., beginning new measurement.

- 40.000** Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist., utilizing 2-point control; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
S17	S16
<hr/>	
S20	S21

2004

Drive a steel fence post alongside stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From this point, an unrecorded iron pipe, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with the marks T41S 17 16 20 21 + visible on south face, bears S. 80°18.6' E., 1.230 chs. dist. The iron pipe does not agree with recovered original cors. in the vicinity to the east and north, no record was recovered to determine who or when the iron pipe was set. The determination was made that the iron pipe was set using incorrect procedures and is not utilized during the course of this resurvey.

Cor. is located on a level area, approximately 530 ft. east of Aneth, Utah sewer lagoon.

From the cor. of secs. 15, 16, 21 and 22.

N. 89°54.5' W., bet. secs. 16 and 21.

- 40.030** The 1/4 sec. cor. of secs. 16 and 21, monumented with an unrecorded rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, in a mound of stone, with a sandstone, 14X13X2 ins., clearly mkd. 1/4 on one face, laying nearby. The rebar is accepted as a careful and faithful perpetuation of the original cor.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
S16
1/4 ———
S21
2004

Bury rebar inside stainless steel post.

Bury mkd. stone alongside stainless steel post.

Cor. is located on a slight SE slope in scattered sagebrush.

N. 89°22.1' W., beginning new measurement.

- 40.002** The cor. of secs. 16, 17, 20 and 21.

From the cor. of 8, 9, 16 and 17, on the auxiliary base line.

N. 0°04.5' W., bet. secs. 8 and 9.

- 40.078** Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
1/4
S8 | S9
2004

Cor. is located on a NW slope.

- 80.156** The cor. of secs. 4, 5, 8 and 9, monumented with a sandstone, 14X10X5 ins., firmly set, dimly mkd. with 5 notches on the south and clearly mkd. with 4 notches on the east edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
S5 | S4
—+—
S8 | S9
2004

Bury mkd. stone alongside stainless steel post.

Cor. is located on sandy S slope and approximately 100 ft. north of wash, drains SW.

From the cor. of secs. 3, 4, 9 and 10.

N. 89°44.3' W., bet. secs. 4 and 9.

- 39.914** Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
S4
1/4 —
S9
2004

Cor. is located on a NW slope, 7 ft. east of a wash, drains N. 10° W.


- 79.828** The cor. of secs. 4, 5, 8 and 9.

N. 0°04.0' W., bet. secs. 4 and 5.

- from which

WC
T41S R25E
1/4
S5 ↑ S4
2004

79.740 The closing cor. of secs. 4 and 5, falls on a ledge, clearly mkd. with chiseled marks:



No remains of reference mound of stone was recovered.

S. $0^{\circ}32.4'$ W., bet. secs. 17 and 18.

- Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R25E
1/4
S18 ↓ S17
WC
2004

Witness cor. is located on flat surface, 20 ft. south of dirt road, bears E-W, 85 ft. west of water well #15.

- 40.000** True point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor., falls within the banks of the San Juan River, unsafe to monument.
- 41.332** Right bank of San Juan River, course N. 38° W.; point for the meander cor. of secs. 17 and 18. Not monumented.
- 50.836** Left bank of San Juan River; point for the meander cor. of secs. 17 and 18. Not monumented.
- 62.234** Left bank of San Juan River, course N. 14° E.; point for the meander cor. of secs. 17 and 18. Not monumented.
- 64.040** Left bank of San Juan River, course N. 39° W.; point for the meander cor. of secs. 17 and 18. Not monumented.
- 80.000** Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist., utilizing 2-point control; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
S18	S17
S19	S20

2004

Cor. is located in flood plain of San Juan River in thick tamarisk.

From the cor. of secs. 16, 17, 20 and 21.

S. 89°35.9' W., bet. secs. 17 and 20.

- 10.915** Right bank of San Juan River, course N. 54° W.; point for the meander cor. of secs. 17 and 20. Not monumented.
- 17.841** Left bank of San Juan River; point for the meander cor. of secs. 17 and 20. Not monumented.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

40.000 Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
S17
1/4 ———
S20
2004

Cor. is located in San Juan River flood plain, in thick Russian olive, tamarisk and cottonwood.

80.000 The cor. of secs. 17, 18, 19 and 20.

From the cor. of secs. 7, 8, 17 and 18, on the auxiliary base line.

N. 0°08.2' W., bet. secs. 7 and 8.

39.929 Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor., falls in the center of an improved gravel road, bears N. 70° E. and S. 70° W.

Set a rebar, 6 ins. long, 5/8 in. diam., 4 ins. below gravel surface.

from which

A chiseled "X", 6 ins. high, on center of sandstone ledge rock, 7 ft. long, 3 ft. high, bears N. 6°58.6' W., 58.2 lks. dist., for a reference object.

A stainless steel post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with magnet at base, in a mound of stone, 3 ft. base, to top, with Navajo brass cap mkd. T41SR25E S7 RM 2004 and an arrow pointing to the cor., bears N. 73°51.7' W., 93.2 lks. dist., for a reference monument.

79.858 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor., falls on a sand dune.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

T41S	R25E
S6	S5
S7	S8

2004

Drive a steel fence post along north side of stainless steel post.

Cor. is located between two power lines, each bearing N. 10° E. and S. 10° W.


From the cor. of secs. 4, 5, 8 and 9.

S. 89°46.5' W., bet. secs. 5 and 8.

- 40.034** True point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor., falls in a slide area, unsafe to monument.

from which

The point selected for the offline witness cor. to the 1/4 sec. cor. of secs. 5 and 8 bears, S. 1°08.9' W., 0.315 chs. dist. to a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground with magnet at base, with Navajo brass cap mkd.:



Note: A suitable point for an online witness cor. was not found within limits.

- 80.068** The cor. of secs. 5, 6, 7 and 8.

N. 89°47.3' W., bet. secs. 6 and 7.

- 40.034** Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor., falls on ledge rock.

At the point, chisel an "X", 4 ins. high. Drive a PK-nail at intersection of chiseled "X". Place a stainless steel post, 30 ins. long, 2 1/2 ins. diam., over chiseled "X" and PK-nail, in a supporting mound of stone, 5 ft. base, to top, with Navajo brass cap mkd.:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R25E
S6
1/4 ———
S7
2004

77.456 The cor. of secs. 1, 6, 7 and 12, on the west bdy. of the tp.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°24.1' W., bet. secs. 5 and 6.

39.930 The 1/4 sec. cor. of secs. 5 and 6, monumented with a sandstone, 15X12X5 ins., loosely set, clearly mkd. 1/4 on west face, with a reference mound of stone to the west.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
1/4
S6 | S5
2004

Bury mkd. stone on north side of stainless steel post.

Rebuild reference mound of stone to 4 ft. base around stainless steel post.

Cor. is located on a slight north slope in sagebrush, 115 ft. S. 30° E. of a dirt road, 7 ft. wide, bears N. 70° E. and S. 70° W.

N. 0°05.6' E., beginning new measurement.

40.139 Point for the closing cor. of secs. 5 and 6, on the south bdy. of T. 40 S., R. 25 E., Eighth Standard Parallel South, hereinbefore described.

Subdivision of Section 27,
T. 41 S., R. 25 E., Salt Lake Meridian, Utah

From the 1/4 sec. cor. of secs. 27 and 34.

N. 0°01.8' E., on the N-S centerline of sec. 27.

40.162 Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E-W centerline of sec. 27.

SUBDIVISION OF SECTION 27,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
C1/4 + S27
2004

Drive a steel fence post along west side of stainless steel post.

Cor. is located 60 ft. south of gravel road, bears E-W.

60.252 Point for the center N 1/16 sec. cor. of sec. 27. Not monumented.

80.342 The 1/4 sec. cor. of secs. 22 and 27.

From the 1/4 sec. cor. of secs. 26 and 27.

N. 89°46.9' W., on the E-W centerline of sec. 27.

Note: The 1973 Manual of Surveying Instructions in Chapter 3-87 states "To subdivide a section into quarter sections, run straight lines from the established quarter-section corners to the opposite quarter-section corners. The point of intersection of the lines thus run will be the corner common to the several quarter sections, or the legal center of the section." In this township, the subdivision of section 27 into quarter sections can not be completed in the normal fashion. The 1899 Page and Lentz survey of a portion of the subdivisional lines did not establish the 1/4 section corner of sections 27 and 28. Section 27 has been determined to be a fractional section. The 1973 Manual of Surveying Instructions in Chapter 3-88 states "The law provides that where opposite corresponding quarter-section corners have not been or cannot be fixed, the subdivision-of-section lines shall be ascertained by running from the established corners north, south, east, or west, as the case may be, to the water course, reservation line, or other boundary of such fractional section, as represented upon the official plat. In this the law presumes that the section lines are due north and south, or east and west lines, but usually this is not the case. Hence, in order to carry out the spirit of the law, it will be necessary in running the centerlines through fractional sections to adopt mean courses where the section lines are not on due cardinal, or to run parallel to the east, south, west, or north boundary of the section, as conditions may require, where there is no opposite section line." The above 2 citations of the 1973 Manual of Surveying Instructions were the basis of establishing the E-W centerline of section 27 on a mean bearing.

SUBDIVISION OF SECTION 27,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

10.002 Point for the C-E-E 1/64 sec. cor. of secs. 27. Not monumented.

15.003 Point for the C-W-E-E 1/256 sec. cor. of sec. 27.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

C W E E
1/256
S27
2004

Drive a steel fence post alongside stainless steel post.

Cor. is located on a W sandy slope, 66 ft. east of draw, drains east.

20.004 Point for the center E 1/16 sec. cor. of secs. 27 Not monumented.

40.008 The center 1/4 sec. cor. of sec. 27.

N. 89°59.9' W., beginning new measurement.

40.004 Point for the 1/4 sec. cor. of secs. 27 and 28, hereinafter described.

From the point for the center E 1/16 sec. cor. of sec. 27.

N. 0°01.0' E., on the N-S centerline of the NE 1/4 of sec. 27.

10.027 Point for the C-S-NE 1/64 sec. cor. of sec. 27. Not monumented.

20.054 Point for the NE 1/16 sec. cor. of sec. 27, at intersection with the E-W centerline of the NE 1/4 of sec. 27. Not monumented.

30.081 Point for the C-N-NE 1/64 sec. cor. of sec. 27. Not monumented.

40.108 Point for the E 1/16 sec. cor. of secs. 22 and 27.

From the N 1/16 sec. cor. of secs. 26 and 27.

N. 89°40.1' W., on the E-W centerline of the NE 1/4 of sec. 27.

4.999 Point for the C-E-E-NE 1/256 sec. cor. of sec. 27. Not monumented.

SUBDIVISION OF SECTION 27,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 9.998** Point for the C-E-NE 1/64 sec. cor. of sec. 27. Not monumented.
- 19.996** The point for the NE 1/16 sec. cor. of sec. 27.
- 39.992** The point for the center N 1/16 sec. cor. of sec. 27.
-

From the point for the C-E-NE 1/64 sec. cor. of sec. 27.

N. 0°00.6' E., on the N-S centerline of the NE 1/4 of the NE 1/4 of sec. 27.

- 5.008** Point for the C-S-NE-NE 1/256 sec. cor. of sec. 27. Not monumented.
- 10.016** Point for the NE-NE 1/64 sec. cor. of sec. 27, at intersection with the E-W centerline of the NE 1/4 of the NE 1/4 of sec. 27. Not monumented.
- 16.556** Point of intersection with the westerly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 51°03.8' E. and N. 51°03.8' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file. Not monumented.
- 17.143** Intersect the centerline of Texas-New Mexico Pipeline Company oil pipe line, bears S. 51°03.8' E. and N. 51°03.8' W.
- 17.726** Intersect the easterly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 51°03.8' E. and N. 51°03.8' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file.
- 20.034** The point for the E-E 1/64 sec. cor. of secs. 22 and 27.
-

From the N-N 1/64 sec. cor. of secs. 26 and 27.

N. 89°37.0' W., on the E-W centerline of the NE 1/4 of the NE 1/4 of sec. 27.

- 0.377** Intersect the easterly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 50°57.7' E. and N. 50°57.7' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file.

SUBDIVISION OF SECTION 27,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 1.109** Intersect the centerline of Texas-New Mexico Pipeline Company oil pipe line, bears S. 50°57.7' E. and N. 50°57.7' W.
- 1.854** Point of intersection with the westerly boundary of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. The right-of-way line bears S. 50°57.7' E. and N. 50°57.7' W. A copy of a portion of the right-of-way map will be placed in the Group 973 file. Not monumented.
- 4.999** Point for the C-E-NE-NE 1/256 sec. cor. of sec. 27. Not monumented.
- 9.998** The point for the NE-NE 1/64 sec. cor. of sec. 27.
- 19.996** The point for the C-N-NE 1/64 sec. cor. of sec. 27.

From the point for the C-E-E-NE 1/256 sec. cor. of sec. 27.

N. 0°00.4' E. on the N-S centerline of the SE 1/4 of the NE 1/4 of the NE 1/4 of sec. 27.

- 5.006** Point for the SE-NE-NE 1/256 sec. cor. of sec. 27, at intersection with the E-W centerline of the SE 1/4 of the NE 1/4 of the NE 1/4 of sec. 27.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

SE-NE-NE 1/256

S27

2004

Drive a steel fence post alongside stainless steel post.

- 10.012** The point for the C-E-NE-NE 1/256 sec. cor. of sec. 27.

From the S-N-N 1/256 sec. cor. of secs. 26 and 27.

N. 89°38.7' W., on the E-W centerline of the SE 1/4 of the NE 1/4 of the NE 1/4 of sec. 27.

- 4.999** The SE-NE-NE 1/256 sec. cor. of sec. 27.
- 9.998** The point for the C-S-NE-NE 1/256 sec. cor. of sec. 27.

From the point for the C-E-E 1/64 sec. cor. of sec. 27.

N. 0°00.6' E., on the N-S centerline of the SE 1/4 of the NE 1/4 of sec. 27.

SUBDIVISION OF SECTION 27,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

- 10.017** Point for the SE-NE 1/64 sec. cor. of sec. 27, at intersection with the E-W centerline of the SE 1/4 of the NE 1/4 of sec. 27.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 30 ins. in the ground with magnet at base, flush with surface, with Navajo brass cap mkd.:

SE-NE 1/64
S27
2004

Cor. is located in parking area north of public meeting house.

- 15.025** Point for the C-N-SE-NE 1/256 sec. cor. of sec. 27.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

S27
C N SE NE
1/64
2004

Drive a steel fence post alongside stainless steel post.

From this point an unrecorded rebar, 5/8 in. diam., firmly set, projecting 3 ins. above ground, bears N. 0°31.6' W., 0.251 chs. dist., set using incorrect procedures and is not utilized during the course of this survey. The rebar appears to have been established in 1992, as part of Exhibit B, dated July 23, 1992. The rebar is not in agreement with Exhibit B, dated July 23, 1992 and unrecorded plat Exhibit A, dated February 9, 1994.

Cor. is located in scattered sagebrush.

- 20.033** The point for the C-E-NE 1/64 sec. cor. of sec. 27.

From the S-N 1/64 sec. cor. of secs. 26 and 27.

N. 89°43.9' W., on the E-W centerline of the SE 1/4 of the NE 1/4 of sec. 27.

- 5.000** Point for the C-E-SE-NE 1/256 sec. cor. of sec. 27. Not monumented.
- 10.000** The SE-NE 1/64 sec. cor. of sec. 27.
- 15.000** Point for the C-W-SE-NE 1/256 sec. cor. of sec. 27, falls in center of dirt road, bears NE-SW, in agreement with Exhibit B, dated July 23, 1992.

SUBDIVISION OF SECTION 27,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a rebar, 8 ins. long, with aluminum cap, 2 ins. diam.,
flush with road surface, aluminum cap mkd.:

C W SE NE
1/256
S27
2004

From this point an unrecorded rebar, 5/8 in. diam., bears
N. 0°55.1' W., 0.235 chs. dist., set using incorrect procedures
and is not utilized during the course of this survey. The
rebar is not in agreement with Exhibit B, dated July 23, 1992
and unrecorded plat Exhibit A, dated February 9, 1994.

20.000 The point for the C-S-NE 1/64 sec. cor. of sec. 27.

From the point for the C-E-SE-NE 1/256 sec. cor. of sec. 27.

N. 0°00.4' E., on the N-S centerline of the NE 1/4 of the SE
1/4 of the NE 1/4 of sec. 27.

5.006 Point for the NE-SE-NE 1/256 sec. cor. of sec. 27, at
intersection with the E-W centerline of the NE 1/4 of the SE
1/4 of the NE 1/4 of sec. 27, falls in residential backyard,
occupied by pit bulls, unsafe to monument.

10.012 The point for the C-E-E-NE 1/256 sec. cor. of sec. 27.

From the point for the N-S-N 1/256 sec. cor. of secs. 26 and
27.

N. 89°42.1' W., on the E-W centerline of the NE 1/4 of the SE
1/4 of the NE 1/4 of sec. 27.

5.000 The point for the NE-SE-NE 1/256 sec. cor. of sec. 27.

10.000 The C-N-SE-NE 1/256 sec. cor. of sec. 27.

From the C-W-E-E 1/256 sec. cor. of sec. 27.

N. 0°00.7' E., on the N-S centerline of the SW 1/4 of the SE
1/4 of the NE 1/4 of sec. 27.

10.022 The C-W-SE-NE 1/256 sec. cor. of sec. 27.

Resurvey of the meanders of the Right Bank of the
San Juan River, through T. 41 S., R. 25 E.,
Salt Lake Meridian, Utah

RESURVEY OF THE MEANDERS OF THE RIGHT BANK
OF THE SAN JUAN RIVER THROUGH,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From the meander cor. of secs. 3 and 34, on the south boundary of the tp., on the right bank of the San Juan River, hereinbefore described.

Thence, with the meanders of the present right bank of the San Juan River through sec. 34.

N. 28°15.6' W., 4.711 chs.

N. 7°58.1' E., 5.085 chs.

N. 11°49.0' W., 3.254 chs.

N. 36°06.5' W., 6.622 chs.

N. 74°00.0' W., 17.691 chs.

N. 56°56.1' W., 7.963 chs.

N. 30°01.6' W., 5.811 chs.

N. 62°34.9' W., 10.790 chs.

N. 37°03.8' W., 0.111 chs. The point for the meander cor. of
secs. 33 and 34. Not monumented.

Thence in sec. 33

N. 37°03.8' W., 8.738 chs.

N. 8°10.1' W., 9.722 chs.

N. 0°05.3' E., 2.447 chs.

N. 30°21.1' E., 9.311 chs.

N. 12°45.7' E., 7.084 chs.

N. 16°29.1' W., 9.388 chs. The point for the meander cor. of
secs. 28 and 33. Not monumented.

Thence in sec. 28

N. 16°29.1' W., 3.095 chs.

N. 39°53.0' W., 7.195 chs.

N. 7°53.4' E., 12.515 chs.

N. 7°37.9' E., 8.137 chs.

N. 25°23.2' W., 9.281 chs.

RESURVEY OF THE MEANDERS OF THE RIGHT BANK
OF THE SAN JUAN RIVER THROUGH,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 14°12.4' W., 6.294 chs.

N. 10°44.5' W., 3.454 chs.

N. 2°50.1' W., 7.434 chs.

N. 34°15.6' W., 1.549 chs.

N. 18°19.4' E., 19.175 chs.

N. 45°22.5' E., 9.363 chs. The point for the meander cor. of
secs. 21 and 28. Not monumented.

Thence in sec. 21

N. 45°22.5' E., 0.647 chs. The point for the meander cor. of
secs. 21 and 22. Not monumented.

Thence in sec. 22

N. 45°22.5' E., 7.114 chs.

N. 1°29.0' W., 2.947 chs.

N. 57°29.9' W., 5.932 chs. The point for the meander cor. of
secs. 21 and 22. Not monumented.

Thence in sec. 21

N. 57°29.9' W., 5.021 chs.

N. 56°03.5' W., 19.480 chs.

N. 41°13.2' W., 6.442 chs.

N. 31°04.9' W., 4.646 chs.

N. 15°08.0' W., 6.136 chs.

N. 0°14.3' W., 3.566 chs.

N. 6°00.6' E., 3.327 chs.

N. 23°57.5' W., 5.426 chs.

N. 48°28.8' W., 4.385 chs.

N. 51°38.9' W., 7.795 chs.

N. 71°36.6' W., 11.959 chs.

N. 64°53.2' W., 8.970 chs.

RESURVEY OF THE MEANDERS OF THE RIGHT BANK
OF THE SAN JUAN RIVER THROUGH,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 76°09.8' E., 6.705 chs.

N. 66°13.9' W., 7.008 chs.

N. 61°58.1' W., 8.870 chs. The point for the meander cor. of
secs. 20 and 21. Not monumented.

Thence in sec. 20

N. 61°58.1' W., 6.002 chs.

N. 74°44.8' W., 4.864 chs.

N. 54°09.5' W., 1.142 chs. The point for the meander cor. of
secs. 17 and 20. Not monumented.

Thence in sec. 17

N. 54°09.5' W., 7.794 chs.

N. 65°49.5' W., 6.952 chs.

N. 77°16.9' W., 7.254 chs.

N. 78°56.2' W., 2.847 chs.

S. 59°40.3' W., 5.123 chs.

N. 85°02.7' W., 12.226 chs.

N. 77°34.9' W., 12.209 chs.

N. 42°51.7' W., 2.069 chs.

N. 23°34.4' W., 10.257 chs.

N. 23°04.6' W., 10.102 chs.

N. 50°21.6' W., 9.078 chs.

N. 38°08.1' W., 1.948 chs. The point for the meander cor. of
secs. 17 and 18. Not monumented.

Thence in sec. 18

N. 38°08.1' W., 2.804 chs.

N. 32°20.4' W., 6.793 chs.

N. 55°14.1' W., 3.400 chs.

RESURVEY OF THE MEANDERS OF THE RIGHT BANK
OF THE SAN JUAN RIVER THROUGH,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 58°21.9' W., 4.612 chs.
 N. 57°35.9' W., 2.491 chs.
 N. 61°17.5' W., 5.625 chs.
 N. 65°01.7' W., 4.340 chs.
 N. 63°40.0' W., 5.874 chs.
 N. 83°27.5' W., 3.884 chs.
 N. 68°12.9' W., 4.525 chs.
 N. 86°45.6' W., 14.348 chs.
 N. 71°01.9' W., 7.593 chs.
 N. 48°07.9' W., 6.304 chs.
 N. 44°56.9' W., 2.398 chs.
 N. 53°22.4' W., 2.689 chs.
 N. 76°57.5' W., 4.015 chs.
 N. 76°13.2' W., 4.914 chs.
 N. 72°49.8' W., 2.263 chs. True point for the meander cor. of
 13 and 18, on the west bdy. of the
 tp.

Survey of the meanders of the left bank of the San Juan
 River through T. 41 S., R. 25 E., Salt Lake Meridian, Utah

From the true point for the meander cor. of secs. 3 and 34, on
 the south boundary of the tp., on the left bank of the San
 Juan River, hereinbefore described.

Thence, with the meanders of the present left bank of the San
 Juan River through sec. 34.

N. 13°27.5' W., 12.916 chs.
 N. 64°25.6' W., 15.767 chs.
 N. 52°37.6' W., 12.976 chs.
 N. 58°49.9' W., 9.612 chs.
 N. 51°13.5' W., 1.613 chs. The point for the meander cor. of
 secs. 33 and 34. Not monumented.

RESURVEY OF THE MEANDERS OF THE LEFT BANK
OF THE SAN JUAN RIVER THROUGH,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Thence in sec. 33

N. 51°13.5' W., 11.402 chs.

N. 14°35.5' W., 19.310 chs.

N. 1°00.3' E., 12.192 chs.

N. 8°20.6' E., 8.859 chs. The point for the meander cor. of
secs. 28 and 33. Not monumented.

Thence in sec. 28

N. 8°20.6' E., 4.985 chs.

N. 2°43.6' W., 13.360 chs.

N. 21°35.7' E., 6.075 chs.

N. 10°27.4' W., 12.631 chs.

N. 14°31.7' W., 14.505 chs.

N. 14°21.9' E., 24.549 chs.

N. 48°06.8' E., 9.189 chs. The point for the meander cor. of
secs. 21 and 28. Not monumented.

Thence in sec. 21

N. 48°06.8' E., 3.949 chs. The point for the meander cor. of
secs. 21 and 22. Not monumented.

Thence in sec. 22

N. 48°06.8' E., 0.873 chs.

N. 11°44.5' E., 3.058 chs.

N. 20°07.2' W., 2.716 chs.

N. 70°19.2' W., 0.368 chs. The point for the meander cor. of
secs. 21 and 22. Not monumented.

Thence in sec. 21

N. 70°19.2' W., 2.744 chs.

N. 57°45.3' W., 20.884 chs.

RESURVEY OF THE MEANDERS OF THE LEFT BANK
OF THE SAN JUAN RIVER THROUGH,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 41°48.5' W., 7.384 chs.
N. 29°06.5' W., 9.553 chs.
N. 9°40.2' W., 11.451 chs.
N. 24°13.3' W., 6.640 chs.
N. 54°11.4' W., 6.831 chs.
N. 78°14.6' W., 14.742 chs.
N. 75°51.4' W., 11.106 chs.
N. 52°56.3' W., 10.255 chs.
N. 66°23.2' W., 7.363 chs. The point for the meander cor. of
secs. 20 and 21. Not monumented.

Thence in sec. 20

N. 66°23.2' W., 3.008 chs.
N. 61°32.1' W., 6.527 chs.
N. 63°04.5' W., 8.993 chs.
N. 52°46.3' W., 1.671 chs. The point for the meander cor. of
secs. 17 and 20. Not monumented.

Thence in sec. 17

N. 52°46.3' W., 5.025 chs.
N. 80°06.2' W., 7.110 chs.
N. 85°03.4' W., 6.376 chs.
S. 89°08.3' W., 1.504 chs.
S. 81°35.8' W., 4.871 chs.
N. 87°46.2' W., 2.086 chs.
N. 81°03.3' W., 19.487 chs.
N. 77°15.4' W., 2.580 chs.
N. 83°13.4' W., 6.960 chs.
N. 59°27.3' W., 4.227 chs.
N. 39°17.0' W., 6.200 chs. The point for the meander cor. of

RESURVEY OF THE MEANDERS OF THE LEFT BANK
OF THE SAN JUAN RIVER THROUGH,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

secs. 17 and 18. Not monumented.

Thence in sec. 18

N. 39°17.0' W., 0.554 chs.

N. 14°57.3' E., 1.426 chs. The point for the meander cor. of
secs. 17 and 18. Not monumented.

Thence in sec. 17

N. 14°57.3' E., 0.334 chs.

N. 43°27.6' E., 3.435 chs.

N. 0°51.9' E., 5.902 chs.

N. 42°12.2' W., 3.619 chs. The point for the meander cor. of
secs. 17 and 18. Not monumented.

Thence in sec. 18

N. 42°12.2' W., 4.471 chs.

N. 15°23.5' W., 5.895 chs.

N. 29°43.0' W., 6.708 chs.

N. 41°19.4' W., 3.696 chs.

N. 59°45.4' W., 13.410 chs.

N. 70°14.6' W., 9.205 chs.

N. 79°05.8' W., 11.142 chs.

N. 85°15.1' W., 11.658 chs.

N. 59°19.9' W., 9.996 chs.

N. 50°28.1' W., 9.251 chs.

N. 80°04.6' W., 5.667 chs.

S. 54°32.0' W., 3.356 chs. The true point for the meander cor.
secs. 13 and 18, on the west bdy.
of the tp.

Metes-and-Bounds survey of westerly boundary of Tract 37,
within Section 27,

T. 41 S., R. 25 E., Salt Lake Meridian, Utah

METES-AND-BOUNDS SURVEY OF WESTERLY BOUNDARY OF TRACT 37, WITHIN
SECTION 27, T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

Note: Tract 37 is a portion of the right-of-way granted the Texas-New Mexico Pipeline Company for an oil pipe line, as shown on the right-of-way map dated November 11, 1957, approved April 13, 1959 by the General Superintendent and on file with the Navajo Agency. Tract 37 is located within sec. 27. A copy of a portion of the right-of-way map will be placed in the Group 973 file.

From Angle Point No. 1, Tract 37, hereinbefore described.

S. 59°01.3' E., on line 1-2.

1.628 Point for Angle Point No. 2.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

AP2
S27 / T37
2004

Cor. is located on SW slope in gravel.

S. 53°53.6' E., on line 2-3.

2.661 Point for Angle Point No. 3.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

AP3
S27 / T37
2004

Cor. is located on SW slope in gravel.

S. 51°03.8' E., on line 3-4.

1.766 Intersect N-S centerline of the NE 1/4 of the NE 1/4 of sec. 27.

4.527 Point for Angle Point No. 4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

METES-AND-BOUNDS SURVEY OF WESTERLY BOUNDARY OF TRACT 37, WITHIN
SECTION 27, T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

AP4
S27 T37
2004

Cor. is located on SW slope in sand and scattered sagebrush.

S. 50°17.2' E., on line 4-5.

3.416 Point for Angle Point No. 5.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

AP5
S27 T37
2004

Cor. is located on SW slope in sand, 50 ft. west of curve in road, 20 ft. wide, concave to the SW.

S. 52°10.8' E., on line 5-6.

2.358 Point for Angle Point No. 6.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

AP6
S27 T37
2004

Cor. is located on SW slope in sand and sagebrush, 9 ft. east of water line valve cover.

S. 50°57.7' E., on line 6-7.

1.954 Intersect E-W centerline of the NE 1/4, NE 1/4 of sec. 27.

2.254 Point for Angle Point No. 7.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

AP7
S27 T37
2004

Cor. is located on SE slope in sand and scattered sagebrush.

METES-AND-BOUNDS SURVEY OF WESTERLY BOUNDARY OF TRACT 37, WITHIN
SECTION 27, T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH
CHAINS

S. 51°13.5' E., on line 7-8.

2.062 Angle point No. 8, hereinbefore described.

Survey of a Portion of the Subdivisional Lines,
T. 41 S., R. 25 E., Salt Lake Meridian, Utah

From the cor. of secs. 3, 4, 33 and 34, on the south bdy. of
the tp., hereinbefore described.

N. 0°02.0' W., bet. secs. 33 and 34.

33.218 Left bank of San Juan River, course N. 51° W.; point for the
meander cor. of secs. 33 and 34. Not monumented.

37.011 Right bank of San Juan River; point for the meander cor. of
secs. 33 and 34. Not monumented.

40.000 True point for the 1/4 sec. cor. of secs. 33 and 34 falls in
the flood plain of the San Juan River in dense Russian olive,
where it is unsafe to monument. There is no suitable location
for an online or offline witness cor. within limits. Not
monumented.

59.249 Point for witness point on line bet. secs. 33 and 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26
ins. in the ground with magnet at base, with Navajo brass cap
mkd.:

T41S R25E
WP
S33 | S34
2004

Cor. is located in Russian olive, outside the flood plain of
the San Juan River.

80.000 Point for the cor. of secs. 27, 28, 33 and 34.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26
ins. in the ground with magnet at base, with Navajo brass cap
mkd.:

T41S R25E
S28 | S27
S33 | S34

2004

Cor. is located in ancient riverbed in tamarisk.

From the angle point bet. secs. 27 and 34.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 89°59.9' W., bet. secs. 27 and 34.

31.007 The cor. of secs. 27, 28, 33 and 34.

N. 0°01.8' E., bet. secs. 27 and 28.

40.159 Point for the 1/4 sec. cor. of secs. 27 and 28.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
1/4
S28 | S27
2004

Cor. is located on flood plain of San Juan River.

80.318 True point for the cor. of secs. 21, 22, 27 and 28, hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33, on the south bdy. of the tp., hereinbefore described.

N. 0°03.0' W., bet. secs. 32 and 33.

40.000 Point for the 1/4 cor. of secs. 32 and 33.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
1/4
S32 | S33
2004

Cor. is located near west rim of spur, projects S.

80.000 Point for the cor. of secs. 28, 29, 32 and 33.

Set a stainless steel post, 30 ins. long, 8 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. base to top, with Navajo brass cap mkd.:

T41S R25E
S29 | S28

S32 | S33
2004

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

From this point an unrecorded galvanized iron pipe, 1 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with galvanized iron cap mkd. T41S R25E S29 S28 S32 S33 COC, bears N. 38°01.0' E., 0.163 chs. dist., set using incorrect procedures and is not utilized during the course of this survey.

Cor. is located in flat drainage area with a series of small washes, draining NW.

From the cor. of secs. 27, 28, 33 and 34.

N. 89°59.7' W., bet. secs. 28 and 33.

- 3.014 Right bank of San Juan River, course N. 37° W.; point for the meander cor. of secs. 28 and 33. Not monumented.
- 12.227 Left bank of San Juan River, point for the meander cor. of secs. 28 and 33. Not monumented.
- 40.022 Point for the 1/4 sec. cor. of secs. 28 and 33.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
S28
1/4 ———
S33
2004

From this point an unrecorded galvanized iron pipe, 1 in. diam., firmly set, projecting 7 ins. above ground, mkd. 1/4 28 33 on one side, bears N. 46°07.1' W., 0.868 chs. dist., set using incorrect procedures and is not utilized during the course of this survey.

Cor. is located on sandy W slope, 130 ft. east of dirt road, bears N-S.

- 80.044 The cor. of secs. 28, 29, 32 and 33.

N. 0°03.0' W., bet. secs. 28 and 29.

- 40.000 Point for the 1/4 sec. cor. of secs. 28 and 29.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
1/4
S29 | S28
2004

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on gentle rolling sandy bench top.

80.000 Point for the cor. of secs. 20, 21, 28 and 29.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock with magnet at base, in a supporting mound of stone, 4 ft. base, to top, with Navajo brass cap mkd.:

T41S	R25E
S20	S21
<hr/>	
S29	S28

2004

Cor. is located on rocky NW slope, approximately 130 ft. east of old bulldozed road.

From the true point for the cor. of secs. 21, 22, 27 and 28,

S. 89°46.7' W., bet. secs. 21 and 28.

0.461 Right bank of San Juan River, course N. 45° E.; point for the meander cor. of secs. 21 and 28. Not monumented.

2.944 Left bank of San Juan River; point for the meander cor. of secs. 17 and 20. Not monumented.

40.070 Point for the 1/4 sec. cor. of secs. 21 and 28.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S	R25E
	S21
1/4	<hr/>
	S28
	2004

Cor. is located in San Juan River flood plain with scattered tamarisk.

80.140 The cor. of secs. 20, 21, 28 and 29.

N. 0°00.8' W., bet. secs. 20 and 21.

40.408 Point for the 1/4 sec. cor. of secs. 20 and 21.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R25E
1/4
S20 | S21
2004

Cor. is located in San Juan River flood plain, in scattered tamarisk and sparsely scattered cottonwood timber.

- 71.292** Left bank of San Juan River, course N. 66° W.; point for the meander cor. of secs. 20 and 21. Not monumented.
- 75.971** Right bank of San Juan River, point for the meander cor. of secs. 20 and 21. Not monumented.
- 80.816** The cor. of secs. 16, 17, 20 and 21.

From the cor. of secs. 5, 6, 31 and 32, on the south bdy. of the tp., hereinbefore described.

N. 0°03.0' W., bet. secs. 31 and 32.

- 40.000** Point for the 1/4 sec. cor. of secs. 31 and 32.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
1/4
S31 | S32
2004

Cor. is located on rocky NW slope, approximately 130 ft. NW of mesa rim.

- 80.000** Point for the cor. of secs. 29, 30, 31 and 32.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground with magnet at base, in a supporting mound of stone, 3 1/2 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E	
S30	S29
<hr/>	
S31	S32

2004

From this point, an unrecorded galvanized iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with galvanized iron cap mkd. 30 29 31 32 COC, bears N. 83°09.4' W., 1.488 chs. dist., set using incorrect procedures and is not utilized during the course of this survey.

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

Cor. is located on top of narrow spur, approximately 160 ft. east of old bulldozed road.

From the cor. of secs. 28, 29, 32 and 33.

N. 89°59.1' W., bet. secs. 29 and 32.

40.007 Point for the 1/4 sec. cor. of secs. 29 and 32.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, in a collar of stone, with Navajo brass cap mkd.:

T41S R25E
S29
1/4 ———
S32
2004

Cor. is located in bottom of small drainage, drains E.

80.014 The cor. of secs. 29, 30, 31 and 32.

N. 89°51.4' W., bet. secs. 30 and 31.

40.000 Point for the 1/4 sec. cor. of secs. 30 and 31.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with Navajo brass cap mkd.:

T41S R25E
S30
1/4 ———
S31
2004

Cor. is located on small sand dune, approximately 160 ft. west of road, bears N-S.

77.098 The cor. of secs. 25, 30, 31 and 35, on the west bdy. of the tp., hereinbefore described.

From the cor. of secs. 29, 30, 31 and 32.

N. 0°03.0' W., bet. secs. 29 and 30.

40.000 Point for the 1/4 sec. cor. of secs. 29 and 30.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R25E
1/4
S30 | S29
2004

Cor. is located on top of sand dune, sloping W.

80.000 Point for the cor. of secs. 19, 20, 29 and 30.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
S19 | S20

S30 | S29
2004

Cor. is located on a NW slope of sand dune.

From the cor. of secs. 20, 21, 28 and 29.

N. 89°59.1' W., bet. secs. 20 and 29.

40.000 Point for the 1/4 sec. cor. of secs. 20 and 29.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground with magnet at base, in a supporting mound of stone, 3 1/2 ft. base, to top, with Navajo brass cap mkd.:

T41S R25E
S20
1/4 -----
S29
2004

Cor. is located on low mesa top bet. two drainages to the N.

80.000 The cor. of secs. 19, 20, 29 and 30.

N. 89°49.6' W., bet. secs. 19 and 30.

40.000 Point for the 1/4 sec. cor. of secs. 19 and 30.

Set a stainless steel post, 30 ins. ling, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

CHAINS

T41S R25E
S19
1/4 ———
S30
2004

Cor. is located on gentle sandy slope, approximately 200 ft. east of main draw.

- 77.003** The cor. of secs. 19, 24, 25 and 30, on the west bdy. of the tp., hereinbefore described.

From the cor. of secs. 19, 20, 29 and 30.

N. 0°01.5' W., bet. secs. 19 and 20.

- 40.118** Point for the 1/4 sec. cor of secs. 19 and 20.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, with magnet at base, in a supporting mound of stone, 4 ft. base to top, with Navajo brass cap mkd.:

T41S R25E
1/4
S19 | S20
2004

Cor. is located on gently rolling plateau above Sand Juan River, and approximately 460 ft. north of E-W dirt road.

- 80.236** The cor. of secs. 17, 18, 19 and 20.

N. 89°59.1' W., bet. secs. 18 and 19.

- 40.000** Point for the 1/4 sec. cor. of secs. 18 and 19.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with magnet at base, with Navajo brass cap mkd.:

T41S R25E
S18
1/4 ———
S19
2004

Cor. is located on the flood plain of the San Juan River.

- 76.947** The cor. of secs. 13, 18, 19 and 24, on the west bdy. of the tp., hereinbefore described.

INFORMATIVE TRAVERSE OF CENTER OF HIGHWAY NO. 262, WITHIN
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

Informative Traverse of Center of Highway No. 262, Within
T. 41 S., R. 25 E., Salt Lake Meridian, Utah

Beginning at a point on the east bdy. of the tp., from which
the cor. of Tps. 41 and 42 S., Rs. 25 and 26 E., bears
S. 0°13.8' E., 33.181 chs. dist.

Thence in sec. 36

N. 70°30.0' W., 2.434 chs.

N. 75°15.0' W., 2.263 chs.

N. 80°15.7' W., 2.960 chs.

N. 86°46.1' W., 3.461 chs.

S. 87°11.1' W., 2.954 chs.

S. 85°05.7' W., 4.807 chs.

N. 87°27.9' W., 5.214 chs.

N. 74°46.9' W., 4.438 chs.

N. 64°15.3' W., 3.542 chs.

N. 53°55.9' W., 4.338 chs.

N. 39°57.8' W., 6.083 chs.

N. 26°19.3' W., 4.359 chs.

N. 15°56.9' W., 26.356 chs.

N. 12°46.2' W., 4.637 chs.

N. 8°57.5' W., 1.371 chs. Point of intersection with the sec.
line bet. secs. 25 and 36, not
monumented. From this point, the
cor. of secs. 25, 26, 35 and 36,
bears S. 89°43.0' W., 30.855 chs.
dist.

Thence in sec. 25

N. 8°57.5' W., 5.813 chs.

N. 5°01.6' W., 7.316 chs.

N. 4°51.3' W., 3.709 chs.

INFORMATIVE TRAVERSE OF CENTER OF HIGHWAY NO. 262, WITHIN
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

N. 5°35.9' W., 3.688 chs.
 N. 14°20.7' W., 3.990 chs.
 N. 27°58.9' W., 3.201 chs.
 N. 42°55.0' W., 4.117 chs.
 N. 59°09.5' W., 4.175 chs.
 N. 75°17.0' W., 3.920 chs.
 S. 89°03.3' W., 3.911 chs.
 S. 75°51.4' W., 2.860 chs.
 S. 68°38.9' W., 4.824 chs.
 S. 69°10.9' W., 3.953 chs.
 S. 76°22.0' W., 1.193 chs. Point of intersection with the sec.
 line bet. secs. 25 and 26, not
 monumented. From this point, the
 cor. of secs. 25, 26, 35 and 36,
 bears S. 0°08.2' E., 29.190 chs.
 dist.

Thence in sec. 26

S. 76°22.0' W., 1.583 chs.
 S. 85°31.9' W., 3.444 chs.
 N. 85°38.3' W., 3.068 chs.
 N. 75°37.7' W., 3.926 chs.
 N. 66°17.2' W., 3.039 chs.
 N. 60°19.4' W., 3.855 chs.
 N. 59°22.2' W., 16.591 chs.
 N. 61°09.8' W., 3.149 chs.
 N. 65°31.9' W., 3.903 chs.
 N. 68°52.4' W., 9.537 chs.
 N. 68°38.5' W., 3.679 chs.
 N. 65°29.4' W., 2.925 chs.
 N. 57°39.3' W., 5.781 chs.

INFORMATIVE TRAVERSE OF CENTER OF HIGHWAY NO. 262, WITHIN
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

N. 50°58.6' W., 24.366 chs.

N. 50°55.8' W., 3.600 chs. Point of intersection with the
sec. line bet. secs. 26 and 27,
not monumented. From this point
the cor. of secs. 22, 23, 26 and
27, bears N. 0°00.2' E.. 8.857 chs.
dist.

Thence in sec. 27

N. 50°55.8' W., 14.186 chs. Point of intersection with the
sec. line bet. secs. 22 and 27,
not monumented. From this point
the 1/4 sec. cor. of secs. 22 and
27 bears N. 89°33.5' W., 28.969
chs.

Thence in sec. 22

N. 50°55.8' W., 64.026 chs.

N. 51°48.6' W., 2.508 chs.

N. 54°53.0' W., 2.768 chs.

N. 59°25.9' W., 4.298 chs.

N. 63°59.4' W., 15.784 chs. Point of intersection with the
sec. line bet. secs. 21 and 22,
not monumented. From this point
the 1/4 sec. cor. of secs. 21 and
22 bears S. 0°04.9' E., 10.136
chs. dist.

Thence in sec. 21

N. 63°59.4' W., 3.263 chs.

N. 61°17.7' W., 2.845 chs.

N. 57°28.2' W., 3.137 chs.

N. 53°18.3' W., 10.155 chs.

N. 53°00.2' W., 4.236 chs.

N. 53°16.0' W., 3.074 chs.

N. 55°06.3' W., 1.568 chs.

N. 58°28.9' W., 3.292 chs.

INFORMATIVE TRAVERSE OF CENTER OF HIGHWAY NO. 262, WITHIN
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

N. 63°20.7' W., 3.758 chs.

N. 68°52.1' W., 30.182 chs. Point of intersection with the
sec. line bet. secs. 16 and 21,
not monumented. From this point
the 1/4 sec. cor. of secs. 16 and
21 bears S. 89°22.1' E., 17.593
chs. dist.

Thence in sec. 16

N. 68°52.1' W., 18.363 chs.

N. 66°14.6' W., 2.807 chs.

N. 60°08.7' W., 3.125 chs. Point of intersection with the sec.
line bet. secs. 16 and 17, not
monumented. From this point the
cor. of secs. 16, 17, 20 and 21
bears S. 0°00.3' E., 9.061 chs.
dist.

Thence in sec. 17

N. 60°08.7' W., 0.321 chs.

N. 53°42.7' W., 3.497 chs.

N. 51°22.5' W., 10.808 chs.

N. 52°35.3' W., 2.964 chs.

N. 59°53.1' W., 3.622 chs.

N. 71°25.8' W., 3.254 chs.

N. 79°25.7' W., 3.660 chs.

N. 87°34.1' W., 4.897 chs.

N. 85°03.9' W., 3.881 chs.

N. 76°19.6' W., 4.018 chs.

N. 69°08.4' W., 2.825 chs.

N. 61°41.3' W., 2.495 chs.

N. 57°30.2' W., 45.403 chs. Point of intersection with the
sec. line bet. secs. 17 and 18,
not monumented. From this point
the cor. of secs. 7, 8, 17 and 18
bears N. 0°32.4' E., 28.006 chs.
dist.

INFORMATIVE TRAVERSE OF CENTER OF HIGHWAY NO. 262, WITHIN
T. 41 S., R. 25 E., SALT LAKE MERIDIAN, UTAH

Thence in sec. 18

N. 57°30.2' W., 10.043 chs.

N. 56°01.0' W., 4.031 chs.

N. 53°21.5' W., 3.868 chs.

N. 49°55.5' W., 5.433 chs.

N. 47°18.1' W., 2.423 chs.

N. 46°47.4' W., 18.834 chs. Point of intersection with the
sec. line bet. secs. 7 and 18,
not monumented. From this point
the 1/4 sec. cor. of secs. 7 and
18 bears S. 89°59.3' W., 5.149
chs. dist.

Thence in sec. 7

N. 46°47.4' W., 19.043 chs.

N. 48°06.3' W., 4.465 chs.

N. 51°03.5' W., 3.751 chs.

N. 53°21.2' W., 3.771 chs.

N. 56°13.2' W., 4.364 chs.

N. 58°51.6' W., 2.794 chs.

N. 60°07.8' W., 14.390 chs.

N. 60°14.3' W., 1.359 chs. Point of intersection with the
sec. line bet. secs. 7 and 12,
T.41 S., Rs. 24 and 25 E., not
monumented. From this point the
1/4 sec. cor. of secs. 7 and 12
bears N. 0°00.8' W., 7.733 chs.
dist. From this same point a brass
cap firmly set in a concrete
cylinder, with brass cap mkd. 50
254+50 65, bears N. 64°50.3' W.,
33.876 chs. dist.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

TOWNSHIP 41 SOUTH, RANGE 25 EAST, SALT LAKE MERIDIAN, UTAH.

FIELD ASSISTANTS

Name	Capacity
Jerry L. Thomas	Cadastral Surveyor
Jaymoe Tapoof	Survey Aide
Matthew M. Peck	Survey Aide
Sterling Profaizer	Survey Aide

CERTIFICATE OF SURVEY

I, **John F. Carroll, Cadastral Surveyor**, hereby certify upon honor that, in pursuance of special instructions bearing the date of the **3rd day of February, 2004**, I have **executed a dependent resurvey of a portion of the south boundary in Township 40 South, Range 24 East (Eight Standard Parallel South), the dependent resurvey of the south boundary in Township 40 South, Range 25 East (Eighth Standard Parallel South), the dependent resurvey of the East, South and West boundaries, the dependent resurvey of a portion of the subdivisional lines, the subdivision of a portion of section 27, the new meander of the right bank of the San Juan River, the original survey of a portion of the subdivisional lines, the original meander of the left bank of the San Juan River, and metes-and-bounds surveys in section 27, Township 41 South, Range 25 East, of the Salt Lake Meridian, in the State of Utah,** which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

02/27/2006

Date

John F. Carroll
(Cadastral Surveyor)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the dependent resurvey of a portion of the south boundary in Township 40 South, Range 24 East (Eight Standard Parallel South), the dependent resurvey of the south boundary in Township 40 South, Range 25 East (Eighth Standard Parallel South), the dependent resurvey of the East, South and West boundaries, the dependent resurvey of a portion of the subdivisional lines, the subdivision of a portion of section 27, the new meander of the right bank of the San Juan River, the original survey of a portion of the subdivisional lines, the original meander of the left bank of the San Juan River, and metes-and-bounds surveys in section 27, Township 41 South, Range 25 East, of the Salt Lake Meridian, Utah, executed by John F. Carroll, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

March 23, 2006

Date _____

Daniel W. Webb

(Chief Cadastral Surveyor for Utah)

~~CERTIFICATE OF TRANSCRIPT~~

I certify that the foregoing transcript of the field notes of the above-described surveys in **T. 41 S., R. 25 E., Salt Lake Meridian, Utah**, is a true copy of the original field notes.

Date _____

(Authorizing Signature)